

Royal® Flushometer 323-1.0

▶ Code Number

3913900

▶ Description

► Flush Cycle

☐ 1.0 gpf/3.8 Lpf

Specifications

Quiet, Concealed, Diaphragm Type, Rough Brass Urinal Flushometer for either left or right hand supply with the following features:

- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- Metal Non-Hold-Open Foot Pedal with Triple Seal Handle Packing
- Vacuum Breaker
- ¾" Female I.P.S. Union Outlet
- ¾" Female Inlet Adapter, Elbow Flush Connection and Spud Coupling for ¾" Concealed Back Spud
- Chrome Plated Exposed Flushometer Parts
- Non-Hold-Open Foot Pedal, Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Diaphragm, Handle Packing and Vacuum Breaker to be molded from PERMEX® Rubber Compound for Chloramine Resistance
- Flush accuracy controlled by CID® technology

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.

• 3/4" I.P.S. Wheel Handle Bak-Chek® Angle Stop


▶ L Dimension

Specify the "L" Dimension for the proper length of the Handle Assembly and Flush Connection. The "L" Dimension is equal to the Wall Thickness (to the nearest whole inch) plus 2³/₄" (70 mm).

► Accessories (Sold Separately)

See Accessories Section of the Sloan catalog for available accessories





► Compliance & Certifications



This space for Architect/Engineer Approval