



Sensor Exposed Flushometer for Floor Mount or Wall Hung Water Closets, 27" Rough in, SMOOTH



ASME



\*Compliances may change based on options selected.

## Features

- Flush volumes start as low as 1.6 gpf/6.0 Lpf
- Water conservation is aided by the ADA-compliant, non-hold-open handle, which prevents toilet from exceeding intended flush volume
- Flush accuracy is controlled by CID™ technology, also enhancing water efficiency
- Integrity of the product is maintained with the vandal-resistant stop cap
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece to accommodate different height requirements
- High chloramine resistant PERMEX synthetic rubber diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

## Finishes

- ☐ Polished Chrome

## Flush Volume

- ☐ 1.28 gpf for Toilet
- ☐ 1.6 gpf for Toilet
- ☐ 3.5 gpf for Toilet

## Variations

- ☐ TP - Trap Primer
- ☐ E - Straight Stop Variation
- ☐ GJ - Ground Joint Stop
- ☐ YO - Angle Stop Bumper
- ☐ YG - Angle Stop Extended Bumper
- ☐ YH - Single Wall Bumper
- ☐ YI - Double Wall Bumper
- ☐ OR - Override Button
- ☐ YJ - Split Ring Pipe Support
- ☐ YK - Solid Ring Pipe Support
- ☐ YL - Split Ring with Seat Bumper Pipe Support
- ☐ XYV - Valve Less Vacuum Breaker
- ☐ O - Offset Vacuum Breaker
- ☐ W - 3/4 inch Flush Connection
- ☐ AFD - Anti-Flood Device
- ☐ DFB - Dual Filtered Bypass Diaphragm
- ☐ DBP - Dual Bypass Diaphragm
- ☐ WWT - Whitworth Thread