

# Sloan® Flushometer 180-1.5

### ▶ Code Number

3782426

#### ▶ Description

Exposed Urinal Flushometer for 11/4" top spud urinals.

# ► Flush Cycle

1.5 gpf / 5.7 Lpf

## ▶ Specifications

Quiet, Exposed, Diaphragm Type, Chrome Plated Urinal Flushometer with the following features:


- High Chloramine Resistant PERMEX® Synthetic Rubber
  Diaphragm with Linear Filtered Bypass and Vortex Cleansing
  Action™
- 1" I.P.S. Screwdriver Bak-Chek® Angle Stop with Vandal Resistant Stop Cap
- Spud Coupling and Spud Flange for 11/4" Top Spud
- Sweat Solder Adapter with Cover Tube and Cast Wall Flange
- Non-Hold-Open Handle and No External Volume Adjustment to Ensure Water Conservation
- Low Consumption flush accuracy
- Diaphragm, Handle Packing and Vacuum Breaker Molded from PERMEX® Rubber Compound for Chloramine Resistance
- ADA Compliant Metal Oscillating Non-Hold-Open Handle

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.

## ► Accessories (Sold Separately)

See Accessories Section of the Sloan catalog for available accessories





► Compliance & Certifications









This space for Architect/Engineer Approval