BASYS® Low Faucets EFX 300.210.0110

▶ Code Number

3324210

Description

Sensor Metering Handwashing Faucet, line powered with battery back-up, double-infrared sensor activated for pre-tempered or hot and cold water operation.

► Faucet Specifications


Sensor-activated, electronic, chrome plated die cast body, handwashing faucet with the following features:

- One tool service
- All wetted components to be stainless steel, engineered thermoplastic, EPDM, and copper or copper alloy
- Solenoid housed in removable carrier that includes supply strainer, serviceable from above deck
- Mechanical mixing, integral to spout, optional
- Vandal resistant spray insert, key housed inside faucet body
- All electronics sealed to IP-67
- Gold plated electrical contacts
- Above deck individual diagnostic indicators for battery life, solenoid condition, and power up mode
- Flexible, high pressure supply hoses, 3/8" compression connections
- Bi-stable magnetic solenoid
- Double infrared sensors with automatic setting feature
- Single hole installation
- Includes all mounting hardware
- Selectable Sloan programmable line purge mode eliminates stagnant water
- Operates from 1 to 125 psi
- Adjustable run time from 0-3600 seconds (Factory set at 10 second maximum run time upon continuous detection)

▶ CALGreen

This BASYS faucet with a 10-second cycle uses 0.083 gallons of water at 0.5 gallons per minute (exceeds minimum CALGreen requirements) or 0.25 gallons of water at 1.5 gallons per minute, depending upon desired flow rate. Additionally, this BASYS faucet is Sloan reprogrammable to use 0.175 gallons of water at 1.5 gallons per minute with a 7-second cycle (exceeds minimum CALGreen requirements).





► BASYS Spec Language

Sloan BASYS model no. EFX-300._____ double infrared sensor-activated electronic handwashing faucet with battery back-up and line purge mode for pre-tempered or hot/cold water supplies. Product to have double infrared sensors with automatic setting feature. Solenoid valve housed in removable carrier that closes water supply upon removal eliminating need to access control stops. Solenoid carrier includes strainer for easy above-deck service. Optional thermostatic mixer complies with ASSE 1070 requirements.

▶ Compliance & Certifications







IAPMO/cUPC, UL (adapters), CE (adapters), Commonwealth of Massachusetts

UPC, IPC, NPC Canada, California Green Building Code (CALGreen), City of Los Angeles Water Efficiency Ordinance

ASME A112.18.1/CSA B125.1, NSF 372, ANSI/UL 1951, ICC/ANSI 117.1

This space for Architect/Engineer Approval



BASYS® Low Faucets EFX 300.210.0110

► Legislative Compliance

Federal Reduction of Lead in Drinking Water Act Law 111-380 (contains no more than 0.25% weighted average lead content), Section 116875 of the California Health & Safety Code, and Vermont Lead Reduction Law (Vermont Act 193).

ADA Compliant

▶ Base Plate Options (Digit 8)

• Base plate for 4" centerset sink

► Special Finish Options* (ordered separately, late 2013)

- Physical Vapor Desposition brushed stainless (Brushed Chrome)
- Physical Vapor Desposition Brushed Nickel
- Physical Vapor Desposition Polished Brass
- * Minimum order quantities and long lead times may apply.
 Please contact Customer Service for details.

► Adapter Options (Digit 9)

- Plug-In Voltage Adapter (US) 100-240 VAC
- Plug-In Voltage Adapter (UK) 100-240 VAC
- Plug-In Voltage Adapter (EU) 90-264 VAC
- Box-Mount Adapter 120 VAC

▶ Image

	Digit 1	Digit 2	Digit 3	Digit 4	Digit 5	Digit 6	Digit 7	Digit 8	Digit 9	Digit 10
Series	Body Type	Power Type	Crown Type	Mixer Type	Sensing Type	Flow Rate	Battery Type	Base Plate	Adapter	Drain Pop-Up
EFX	3 = Low IR	0 = Hardwire	0 = Bowed	0 = None	0 = Active IR	0 = 0.5 gpm Multi-Lam	0 = Alkaline	0 = None	0 = None	0 = No
				1 = BDM		2 = 1.5 gpm Aerated		1 = 4"	1 = EAF11	1 = Yes
				2 = BDT		3 = 1.5 gpm Laminar		2 = 8"	2 = EAF39	
				5 = ISM					3 = EAF41	
									4 = EAF37	
	Гуре Options И – Mechanica	(Digit 4) I, below deck mixir	ng valve		Options (Digit 8) ate for 4" centerse				ordered separate	
			ng valve							
BDI	M – Mechanica Γ – Thermostati	l, below deck mixir ic, below deck mixi		☐ Base pl	ate for 4" centerse ate for 8" centerse	rt sink	□ PVDSF-I	Physical Vapor De Physical Vapor	sposition Satin Fin Desposition Bru	ish (Brushed Ch shed Nickel
BDI BDI	M – Mechanica F – Thermostati I – Integral side	l, below deck mixir ic, below deck mixi mixer		Base pl Base pl Adapter O	ate for 4" centerse ate for 8" centerse ptions (Digit 9)	et sink et sink	□ PVDSF-I	Physical Vapor De Physical Vapor	sposition Satin Fin	ish (Brushed Ch shed Nickel
BDI BDI	M – Mechanica Γ – Thermostati	l, below deck mixir ic, below deck mixi mixer		Base pl Base pl Adapter O	ate for 4" centerse ate for 8" centerse ptions (Digit 9)	rt sink	PVDSF-I PVDBN- PVDPB-	Physical Vapor De Physical Vapor Physical Vapor I or quantities an	sposition Satin Fin Desposition Brus Desposition Polis and long lead time	ish (Brushed Ch shed Nickel shed Brass
BDI BD' BD' ISN Flow R	M – Mechanica F – Thermostati I – Integral side ate Options (l, below deck mixir ic, below deck mixi mixer		Base pl Base pl Adapter O EAF-11	ate for 4" centerse ate for 8" centerse ptions (Digit 9) — Plug-In Voltage A	et sink et sink	PVDSF-I PVDBN- PVDPB-	Physical Vapor De Physical Vapor Physical Vapor I or quantities an	sposition Satin Fin Desposition Bru Desposition Poli:	ish (Brushed Ch shed Nickel shed Brass
BDI BD' BD' ISN Flow R 0.5	M – Mechanica F – Thermostati I – Integral side ate Options (l, below deck mixir ic, below deck mixi mixer Digit 6) ulti-Lam Spray		Base pl Base pl Adapter O EAF-11 EAF-39	ate for 4" centerse ate for 8" centerse ptions (Digit9) Plug-In Voltage A Plug-In Voltage	et sink et sink Adapter (US) 100-240 VAC	PVDSF-I PVDBN- PVDPB- * Minimum ord Please contact	Physical Vapor De Physical Vapor Physical Vapor I or quantities an	sposition Satin Fin Desposition Brus Desposition Polis ad long lead time vice for details.	ish (Brushed Ch shed Nickel shed Brass
□ BDI □ BD □ ISN Flow R □ 0.5 □ 1.5	M – Mechanica F – Thermostati I – Integral side ate Options (gpm/1.9 Lpm M	I, below deck mixir ic, below deck mixi mixer Digit 6) ulti-Lam Spray erated Stream		Base pl Base pl Adapter O EAF-11 EAF-39 EAF-41	ate for 4" centerse ate for 8" centerse ptions (Digit9) Plug-In Voltage A Plug-In Voltage	nt sink Adapter (US) 100-240 VAC Adapter (UK) 100-240 VAC Adapter (EU) 90-284 VAC	PVDSF-I PVDBN- PVDPB- * Minimum ord Please contac	Physical Vapor De Physical Vapor Physical Vapor I er quantities an t Customer Sen (ordered separ	sposition Satin Fin Desposition Brus Desposition Polis ad long lead time vice for details.	ish (Brushed Ch shed Nickel shed Brass as may apply.
□ BDI □ BD □ ISN Flow R □ 0.5 □ 1.5	M – Mechanica F – Thermostati I – Integral side ate Options (gpm/1.9 Lpm M gpm/5.7 Lpm A	I, below deck mixir ic, below deck mixi mixer Digit 6) ulti-Lam Spray erated Stream		Base pl Base pl Adapter O EAF-11 EAF-39 EAF-41	ate for 4" centerse ate for 8" centerse iptions (Digit 9) — Plug-In Voltage A — Plug-In Voltage A — Plug-In Voltage A	nt sink Adapter (US) 100-240 VAC Adapter (UK) 100-240 VAC Adapter (EU) 90-284 VAC	PVDSF-I PVDBN- PVDPB- * Minimum ord Please contac Accessories EAF-23-	Physical Vapor De Physical Vapor Physical Vapor I er quantities an t Customer Sen (ordered separ	sposition Satin Fin Desposition Brus Desposition Polis and long lead time vice for details. ately) d in hardwire les	ish (Brushed Ch shed Nickel shed Brass as may apply.
□ BDI □ BD □ ISN Flow R □ 0.5 □ 1.5	M – Mechanica F – Thermostati I – Integral side ate Options (gpm/1.9 Lpm M gpm/5.7 Lpm A	I, below deck mixir ic, below deck mixi mixer Digit 6) ulti-Lam Spray erated Stream		Base pl Base pl Adapter O EAF-11 EAF-39 EAF-41	ate for 4" centerse ate for 8" centerse iptions (Digit 9) — Plug-In Voltage A — Plug-In Voltage A — Plug-In Voltage A	nt sink Adapter (US) 100-240 VAC Adapter (UK) 100-240 VAC Adapter (EU) 90-284 VAC	PVDSF-I PVDBN- PVDPB- * Minimum ord Please contac Accessories EAF-23- EAF-24-A	Physical Vapor De Physical Vapor Physical Vapor I er quantities ar t Customer Sen (ordered separ Splitter (include	sposition Satin Fin Desposition Brus Desposition Polision Polision and long lead time vice for details. ately) d in hardwire lession Cable	ish (Brushed Ch shed Nickel shed Brass as may apply.

► Electrical Specifications

- Control Circuit 6.75 VDC
- Power Supplies Optional voltage adapters handle 100-264 VAC and 6 VDC Alkaline Battery Pack
- Sensor Range Factory Setting: 4"- 5" (102-127 mm) Nominal Range Adjustment: 1"- 6" (25-150 mm) Nominal

► Accessories (ordered separately)

- Splitter (included in hardwire less adapter)
- 126" Extension Cable
- 11 13/16" Extension Cable
- 47 1/4" Extension Cable

► ROUGH-IN DIAGRAM

