



Manual Concealed Flushometer for Wall Hung Urinals, Concealed Rear Spud Foot Pedal



\*Compliances may change based on options selected.

## Features

- High chloramine resistant PERMEX synthetic rubber diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

## Finishes

- ☐ Polished Chrome
- ☐ Rough Brass

## Flush Volume

- ☐ 0.125 gpf for Urinal
- ☐ 0.25 gpf for Urinal
- ☐ 0.50 gpf for Urinal
- ☐ 1.0 gpf for Urinal
- ☐ 1.5 gpf for Urinal

## Variations

- ☐ TP - Trap Primer
- ☐ E - Straight Stop Variation
- ☐ K - Wheel Handle Stop Variation
- ☐ GJ - Ground Joint Stop
- ☐ YO - Angle Stop Bumper
- ☐ YG - Angle Stop Extended Bumper
- ☐ YH - Single Wall Bumper
- ☐ YI - Double Wall Bumper
- ☐ FW - Fixture Wall Actuator
- ☐ HL - 3" Push Button, Front of Valve
- ☐ J - Metal Osculating Handle
- ☐ L - 3" Push Button
- ☐ MBFW - Metal Button, Fixture Wall
- ☐ MBPM - Metal Button, Panel Mount
- ☐ MP - Metal Partition Actuator
- ☐ SW - Side Wall Actuator
- ☐ YJ - Split Ring Pipe Support
- ☐ YK - Solid Ring Pipe Support
- ☐ YL - Split Ring with Seat Bumper Pipe Support
- ☐ XYV - Valve Less Vacuum Breaker
- ☐ O - Offset Vacuum Breaker
- ☐ 1" Flush Connection
- ☐ W - 3/4 inch Flush Connection
- ☐ DFB - Dual Filtered Bypass Diaphragm
- ☐ DBP - Dual Bypass Diaphragm
- ☐ H - Handle on front
- ☐ WWT - Whitworth Thread
- ☐ C - Inlet on Left Side of Valve