

OPTIONS

Flush Volume

1.6 gpf (6.0 Lpf) (1.6) 1.28 gpf (4.8 Lpf) (1.28)

Wall Plate Finish

Stainless Steel (BSS)

Water Efficiency

Low Consumption High Efficiency

Bypass

Dual-Filtered Fixed Bypass Diaphragm (DFB)

L Dimension

6 ¾" (171mm) (6-3/4-LDIM)

10 3/4" (273mm) (10-3/4-LDIM)

12 3/4" (324mm) (12-3/4-LDIM)

5 3/4" (146mm) (5-3/4-LDIM)

8 3/4" (222mm) (8-3/4-LDIM)

11 3/4" (298mm) (11-3/4-LDIM)

4 3/4" (121mm) (4-3/4-LDIM)

7 3/4" (197mm) (7-3/4-LDIM)

9 3/4" (248mm) (9-3/4-LDIM)

Wall Box

Standard (not included, order separately)

Push Button

3" Metal Oscillating (L3)

Outlet Tube

Trap Primer (TP)

Compliances & Certifications

BAA Compliant

cUPC Certified

ADA Compliant

BREEAM Water Credit

Green Globes Water Credit

LEED V4 Water Efficiency Credit

Satisfies LEED Credits

WaterSense Listed

cUPC Green Certified

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice



DESCRIPTION

Sloan® Concealed Manual Flushometer

FEATURES

- Flush volumes start as low as 1.6 gpf/6.0 Lpf
- Water conservation is aided by the ADA-compliant, non-holdopen handle
- Flush accuracy is controlled by CID™ technology, also enhancing water efficiency
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece to accommodate different height requirements
- High chloramine resistant PERMEX synthetic rubber diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- Sloan Concealed Installation Instructions
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Concealed Flushometers Repair and Maintenance Guide
- Additional Downloads