

## ► Code Number

3070050

## Description

Exposed, Battery Powered, Side Mount Sensor Operated Water Closet Flushometer for floor mounted or wall hung top spud bowls.

## Flush Cycle

Model 111-SMO Low Consumption (1.6 gpf/6.0 Lpf)

## Specifications

Quiet, Exposed, Piston Type, Chrome Plated Closet Flushometer with the following features:

- Vacuum Breaker Flush Connection
- Fixed Volume Piston with Filtered O-ring Bypass
- 1" I.P.S. Screwdriver Bak-Chek® Angle Stop with Locking Vandal Resistant Stop Cap
- Chrome Plated Infrared Sensor Housing
- "User in View" Flashing LED
- No External Volume Adjustment to Ensure Water Conservation
- Infrared Sensor Range Adjustment Screw and Reset Button
- Diaphragm, Stop Seat and Vacuum Breaker Molded from PERMEX® Rubber Compound for Chloramine Resistance
- Four (4) Size C Batteries included
- ADA Compliant OPTIMA® Battery Powered Infrared Sensor for automatic "No Hands" operation
- Angled Sensor Window
- Manual Override Flush Button
- "Low Battery" Flashing LED with Optional Audio Tone
- Optional 24-Hour Sentinel Flush
- EBV-157 Handle Adapter Kit
- "Spud Coupling, Wall and Spud Flanges for 1½" Top Spud"

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037, ANSI/ASME A112.19.2.

## Accessories (Sold Separately)

- See Accessories Section and OPTIMA Accessories Section of the Sloan catalog for details on these and other OPTIMA® Flushometer variations.



## ► FEATURES

### Automatic Operation

- Sloan OPTIMA SMO equipped Flushometers provide the ultimate in sanitary protection and automatic operation. There is no need for AC hookups or wall alterations. The Flushometer operates by means of a battery powered infrared sensor. Once the user enters the sensor's effective range and then steps away, the Side Mount Unit initiates the flushing cycle to flush the fixture.

### Economical

- Automatic operation provides water usage savings over other flushing devices. Reduces maintenance and operation costs. Installation does not require turning off water to the valve.

### Hygienic

- User makes no physical contact with the Flushometer surface except to initiate the Override Button when required. Helps control the spread of infectious diseases.

## ► Compliance & Certifications



This space for Architect/Engineer Approval

## ► VISUAL INDICATOR GUIDE

## Gem2® Optima® SMO® Exposed Battery-Powered Side-Mount Sensor-Activated Flushometer 111 SMO

### ► ELECTRICAL SPECIFICATIONS

#### Control Circuit

- Solid State
- 6 VDC Input

#### Indicator Lights

- User in View

#### Sensor Type

- Infrared Convergence Type Object Lock Detection

#### Sensor Range

- Nominal 8" - 54" (203 mm - 1372 mm), Factory Set at 24" (610 mm)

#### Battery Type

- (4) C Alkaline

#### Battery Life

3 Years @ 4,000 Flushes/Month

#### Operating Pressure


- 15-100 psi (104-689 kPa)

**USER-IN-VIEW L.E.D.** — Green light flashes 3 times after 5 second delay when a user is in view. The green light flashes constantly when a user is in view during the 7 minute start up sequence.


**BATTERY L.E.D.** — Yellow light flashes indicating it is time to replace batteries with four (4) new Type "C" batteries.

**OBJECT LOCK SENSOR** — Detects user or object.

**COURTESY MANUAL FLUSH BUTTON** — Allows manual activation of flush when needed.




### ► FUNCTION SETTINGS



### ► OPERATION


1. A continuous, invisible light beam is emitted from the Object Lock Infrared Sensor.




2. As the user enters the beam's effective range, 8" to 54" (203 mm - 1372 mm), the Object Lock Infrared Sensor senses the user.



3. When the user steps away from the Object Lock Infrared Sensor, the circuit initiates the flushing cycle to flush the fixture. The Circuit then automatically resets and is ready for the next user.



### ► ROUGH-IN



Includes EBV-89-A Side Mount Operator

Includes EBV-89-A Side Mount Operator