

# Sloan® Flushometer 115-1.28 DFB

#### ▶ Code Number

3780331

#### ► Flush Cycle

1.28 gpf/4.8 Lpf

#### ▶ Description

Exposed Water Closet Flushometer for floor mounted or wall hung top spud bowls.

#### Specifications

Quiet, Exposed, Diaphragm Type, Chrome Plated Closet Flushometer with the following features:


- Vacuum Breaker with Flush Connection
- Spud Coupling and Spud Flange for 11/2" Top Spud
- Sweat Solder Adapter with Cover Tube and Cast Wall Flange
- Non-Hold-Open Handle and No External Volume Adjustment to Ensure Water Conservation
- Diaphragm, Handle Packing and Vacuum Breaker Molded from PERMEX® Rubber Compound for Chloramine Resistance
- ADA Compliant Metal Oscillating Non-Hold-Open Handle

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.

### ► Accessories (Sold Separately)

See Accessories Section of the Sloan catalog for available accessories





## ► Compliance & Certifications









This space for Architect/Engineer Approval