

# **CODE NUMBER**

24601312

#### **DESCRIPTION**

ST-2469 Water Closet and ROYAL 152 ESS Hardwired Flushometer.

# **COMPONENTS**

Flushometer: Code 3451658Water Closet: Code 2102469

# **DETAILS**

• Flush Volume: 1.28 gpf (4.8 Lpf)

 Nominal Dimensions: 26 183/250" × 15 63/500" × 16 183/250" (679 × 384 × 425mm)

# **FLUSHOMETER FEATURES**

- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- Handle Packing, Main Seat, Stop Seat and Vacuum Breaker Molded from PERMEX® Rubber Compound for Chloramine resistance
- User friendly three (3) second Flush Delay
- Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- OPTIMA® EL-1500 Self-Adaptive Infrared Sensor with Indicator Light
- 13 1/2" x 13 1/2" Wall Box with Stainless Steel Access Panel and Vandal Resistant Screws
- Courtesy FlushTM Override with waterproof stainless steel piezoelectric button
- Wall Box with Stainless Steel Access Panel and Vandal Resistant Screws
- High Back Pressure Vacuum Breaker Flush Connection and Spud Coupling for 1-1/2" Concealed Back Spud
- 1" I.P.S. Wheel Handle Bak-Chek® Angle Stop

# **FIXTURE FEATURES**

- White Vitreous China
- Elongated bowl
- Wall mounted, wall outlet
- Siphon jet flushing action achieves 1000g Map score when used with any Sloan flushometer
- Static load rating of 750 lbs (see Notes)
- Water spot area: 101/8" x 93/8" (26 cm x 24 cm)
- 1½ I.P.S. rear spud inlet
- 21/8" fully glazed trapway
- Closet bolts and caps included
- Toilet seat not included



# **COMPLIANCES & CERTIFICATIONS**













(WaterSense Listed, Satisfies LEED Credits, cUPC Certified, cUPC Green Certified, BAA Compliant, ADA Compliant)

# **DOWNLOADS**

- Royal/Sloan/Crown SWB ESS Installation Instructions
- ST-2469 Installation Instructions
- Additional Downloads

# **NOTES**

All information contained within this document subject to change without notice.

Static load tested according to the procedure in Section 6.7 of ASME A112.19.2. Not recommended for bariatric use.



# **ROUGH-IN**

