

► Code Number

3324317

► Description

Sensor Metering Handwashing Faucet, battery powered, double-infrared sensor activated for pre-tempered or hot and cold water operation.

► Flow Rates

1.5 gpm / 5.7 Lpm – Spray Head

► Faucet Specifications

- One tool service
- All wetted components to be stainless steel, engineered thermoplastic, EPDM, and copper or copper alloy
- Solenoid housed in removable carrier that includes supply strainer, serviceable from above deck
- Mechanical mixing, integral to spout, optional
- Vandal resistant spray insert, key housed inside faucet body
- All electronics sealed to IP-67
- Gold plated electrical contacts
- Above deck individual diagnostic indicators for battery life, solenoid condition, and power up mode
- Flexible, high pressure supply hoses, 3/8" compression connections
- Bi-stable magnetic solenoid
- Double infrared sensors with automatic setting feature
- Single hole installation
- Includes all mounting hardware
- Selectable Sloan programmable line purge mode eliminates stagnant water
- Operates from 1 to 125 psi
- Adjustable run time from 0-3600 seconds (Factory set at 10 second maximum run time upon continuous detection)
- Battery powered, sensor-activated, electronic, chrome plated die cast body, handwashing faucet with the following features:
- Faucet can be configured to add solar or solar and LCD display
- Four (4) "AA" alkaline batteries

► Variations

Solar


LCD

► CALGreen

This BASYS faucet with a 10-second cycle uses 0.083 gallons of water at 0.5 gallons per minute (exceeds minimum CALGreen requirements) or 0.25 gallons of water at 1.5 gallons per minute, depending upon desired flow rate. Additionally, this BASYS faucet is Sloan reprogrammable to use 0.175 gallons of water at 1.5 gallons per minute with a 7-second cycle (exceeds minimum CALGreen requirements).



Model EFX-377-000-0000 Shown



► Legislative Compliance

Federal Reduction of Lead in Drinking Water Act Law 111-380 (contains no more than 0.25% weighted average lead content), Section 116875 of the California Health & Safety Code, and Vermont Lead Reduction Law (Vermont Act 193).

► Compliance & Certifications



UPC, IPC, NPC Canada, California Green Building Code (CALGreen), City of Los Angeles Water Efficiency Ordinance

IAPMO/cUPC, Commonwealth of Massachusetts

ASME A112.18.1/CSA B125.1, NSF 372, ANSI/UL 1951, ICC/ANSI 117.1

This space for Architect/Engineer Approval

Model Creation Guide EFX-3

Body Type	Power	Crown	Mix	Sensing	Flow Rate	Battery Type	Base Plate	Voltage Adapters	Drain Pop-Up	Finishes
0	-	☐ Hardwire ☐ Std Bowed	☐ None ☐ Below Deck, Mechanical	Active IR	☐ 0.5 gpm Multi-Lam	Alkaline	☐ None	☐ None	☐ No	☐ CP
1	-	-	-	-	-	-	☐ 4"	☐ Plug-In	-	☐ PVDSF
2	-	-	☐ Below Deck, Thermostatic	-	☐ 1.5 gpm Aerated & Laminar	-	☐ 8"	☐ Plug-In UK	-	-
3	Pedestal	-	-	-	-	-	-	☐ Plug-In EU	-	-
4	-	-	-	-	-	-	-	☐ Box Mount	-	-
5	-	☐ Battery ☐ Solar	☐ Integral Side Mixer	-	-	-	-	-	-	-
6	-	-	☐ LCD	-	-	-	-	-	-	-
7	-	☐ Solar ☐ Solar + LCD	-	-	-	-	-	-	-	-

► Electrical Specifications


- Control Circuit – 6.75 VDC
- Sensor Range – Nominal: 4"- 5" (102-127 mm) Faucet Adaptive Self-Adjustment Range: 2"- 14" (51-356 mm) nominal
- Battery Life – 3-years under worst case conditions of 8,000 cycles per month and high water pressure
- Power Supplies – 6 VDC Alkaline Battery Pack

► Special Finish Options* (ordered separately)

- Physical Vapor Deposition brushed stainless (Brushed Chrome)
- Physical Vapor Deposition Brushed Nickel
- Physical Vapor Deposition Polished Brass
- * Minimum order quantities and long lead times may apply. Please contact Customer Service for details.


► ROUGH-IN

EFX-350.X0X.000X Faucet with Single Line Water Supply



* One (1) Faucet Per Battery Pack

EFX-300.X0X.001X Faucet with Hot/Cold Water Supply



† Up to Six (6) Faucets on One (1) Voltage Adapter