



Manual Exposed Flushometer for Floor Mount or Wall Hung Water Closets, 11.5" Rough in, Rear Spud



*Compliances may change based on options selected.

Features

- Flush volume is factory set with option of adjusting volume range according to specific needs
- Flushing control mechanism functions in oil and is isolated from debris
- Water pressure not required to positively shut off
- Complies with military specifications
- Regulating screw for flush duration control and adjustable tailpiece accommodates different heights
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

Finishes

- ☐ Polished Chrome

Flush Volume

- ☐ 1.28 gpf for Toilet
- ☐ 1.6 gpf for Toilet
- ☐ 3.5 gpf for Toilet

Variations

- ☐ TP - Trap Primer
- ☐ E - Straight Stop Variation
- ☐ K - Wheel Handle Stop Variation
- ☐ GJ - Ground Joint Stop
- ☐ YO - Angle Stop Bumper
- ☐ YG - Angle Stop Extended Bumper
- ☐ YH - Single Wall Bumper
- ☐ YI - Double Wall Bumper
- ☐ HL - 3" Push Button, Front of Valve
- ☐ J - Metal Osculating Handle
- ☐ L - 3" Push Button
- ☐ YJ - Split Ring Pipe Support
- ☐ YK - Solid Ring Pipe Support
- ☐ YL - Split Ring with Seat Bumper Pipe Support
- ☐ XYV - Valve Less Vacuum Breaker
- ☐ O - Offset Vacuum Breaker
- ☐ 1" Flush Connection
- ☐ W - 3/4 inch Flush Connection
- ☐ H - Handle on front
- ☐ WWT - Whitworth Thread
- ☐ C - Inlet on Left Side of Valve