

Code Number

3782654

Description

Exposed Urinal Flushometer for 3/4" top spud urinals.

Flush Cycle

1.0 gpf/3.8 Lpf

Specifications

Quiet, Exposed, Diaphragm Type, Chrome Plated Urinal Flushometer with the following features:

- High Chloramine Resistant PERMEX® Synthetic Rubber Diaphragm with Linear Filtered Bypass and Vortex Cleansing Action™
- ¾" I.P.S. Screwdriver Bak-Chek® Angle Stop with Vandal Resistant Stop Cap
- Vacuum Breaker with Flush Connection
- Spud Coupling and Spud Flange for 3/4" Top Spud
- Sweat Solder Adapter with Cover Tube and Cast Wall Flange
- Non-Hold-Open Handle and No External Volume Adjustment to Ensure Water Conservation
- Low Consumption flush accuracy
- Diaphragm, Handle Packing and Vacuum Breaker Molded from PERMEX® Rubber Compound for Chloramine Resistance
- ADA Compliant Metal Oscillating Non-Hold-Open Handle

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.


Variations

SG SaniGuard® Antimicrobial Coating Protects Handle* * SaniGuard does not protect users or others against disease-causing bacteria.

Accessories (Sold Separately)

See Accessories Section of the Sloan catalog for available accessories





Disclaimer

All information contained within this document subject to change without notice.

F

Compliance & Certifications Made In The

JSA



UPC

This space for Architect/Engineer Approval