Naval® Flushometers



▶ Code Number

3140117

Description

Exposed Water Closet Flushometer for top inlet squat toilets. Especially suited for harsh water conditions.

▶ Flush Cycle

• Model 136-1.6 (Factory set at 1.6 gpf/6.0 Lpf)

Valve Adjustment Range: 1.5 gpf/5.7 Lpf to 7.0 gpf/26.5 Lpf

Specifications

Quiet, Exposed, Adjustable Piston Type, Chrome Plated Closet Flushometer with the following features:

- Trap Primer
- ADA Compliant Metal Oscillating Non-Hold-Open Handle
- Vacuum Breaker Flush Connection
- Self-cleaning Xpelor® Bypass
- 1" I.P.S. Screwdriver Bak-Chek™ Angle Stop with Vandal Resistant Stop Cap
- Spud Coupling and Flange for 11/2" Top Spud
- Stamped Wall Flange
- Ultra High Copper, Low Zinc Brass Castings for Dezincification and Salt Water Resistance
- Handle Packing, Stop Seat and Vacuum Breaker to be Molded from PERMEX® Rubber Compound for Chloramine Resistance

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037, ANSI/ASME 112.19.2.

▶ L Dimension

Specify the "L" Dimension for the proper length of the Handle Assembly and Flush Connection. The "L" Dimension is equal to the Wall Thickness (to the nearest whole inch) plus 23/4" (70 mm).

▶ Variations

- YJ Split Ring Pipe Support
- Solid Ring Pipe Support
- Less Vacuum Breaker
- Sweat Solder Adapter Kit
- Sweat Solder Adapter & Cast Wall Flange with Set Screw
- Ground Joint Stop and Tailpiece
- 11/4" Flush Connection and Spud Coupling"


"NOTE: Bak-Chek™ Angle Stop available with 1'"' Whitworth Thread (please specify)."


► Accessories (Sold Separately)

See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.

▶ Product Number

136-1.6





► Compliance & Certifications



This space for Architect/Engineer Approval