



Manual Exposed Flushometer for Floor Mount or Wall Hung Water Closets, Concealed Rear Spud



ASME



*Compliances may change based on options selected.

Features

- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

Finishes

- ☐ Rough Brass

Flush Volume

- ☐ 1.28 gpf for Toilet
- ☐ 1.6 gpf for Toilet
- ☐ 3.5 gpf for Toilet

Variations

- ☐ TP - Trap Primer
- ☐ E - Straight Stop Variation
- ☐ K - Wheel Handle Stop Variation
- ☐ GJ - Ground Joint Stop
- ☐ YO - Angle Stop Bumper
- ☐ YG - Angle Stop Extended Bumper
- ☐ YH - Single Wall Bumper
- ☐ YI - Double Wall Bumper
- ☐ FW - Fixture Wall Actuator
- ☐ HL - 3" Push Button, Front of Valve
- ☐ J - Metal Osculating Handle
- ☐ L - 3" Push Button
- ☐ MBFW - Metal Button, Fixture Wall
- ☐ MBPM - Metal Button, Panel Mount
- ☐ MP - Metal Partition Actuator
- ☐ SW - Side Wall Actuator
- ☐ YJ - Split Ring Pipe Support
- ☐ YK - Solid Ring Pipe Support
- ☐ YL - Split Ring with Seat Bumper Pipe Support
- ☐ XYV - Valve Less Vacuum Breaker
- ☐ O - Offset Vacuum Breaker
- ☐ 1" Flush Connection
- ☐ W - 3/4 inch Flush Connection
- ☐ H - Handle on front
- ☐ WWT - Whitworth Thread
- ☐ C - Inlet on Left Side of Valve

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 1-800-9-VALVE-9 or 1-847-671-4300

Fax: 1-800-447-8329 or 1-847-671-4380

<http://www.sloan.com>