

Sloan® Bedpan Washers WES BPW 1100

Code Number

3729725

Description

Sloan® Bedpan Washer Water Closet Flushometer for floor mounted or wall hung top spud bowls. Installation meets ADA height requirements.

► Flush Cycle

1.1 to 1.6 gpf/ 4.2 to 6.0 Lpf

Specifications

Quiet, Exposed, Diaphragm Type, Chrome Plated Closet Flushometer with the following features:

- High Chloramine Resistant PERMEX® Synthetic Rubber Diaphragm with Linear Filtered Bypass and Vortex Cleansing Action™
- ADA Compliant Metal Oscillating Non-Hold-Open Handle with Triple Seal Handle Packing
- 1" I.P.S. Screwdriver Bak-Chek® Angle Stop
- Vandal Resistant Stop Cap
- Vacuum Breaker with Flush Connection
- Spud Coupling and Spud Flange for 1½" Top Spud
- Sweat Solder Adapter with Cover Tube and Cast Wall Flange
- Non-Hold-Open Handle and No External Volume Adjustment to Ensure Water Conservation
- Low Consumption flush accuracy
- Diaphragm, Handle Packing and Vacuum Breaker Molded from PERMEX® Rubber Compound for Chloramine Resistance

Bedpan Washer Diverter Assembly with the following features:

- Solid One-piece Body Construction
- Solid Brass Spray Arm
- Counter Balanced Pivot Assembly and Diverter Valve Wall
 Support
- Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass.
 Valve shall be in compliance to the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2. Installation conforms to ADA requirements.


Valve Body, Cover and Tailpiece shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037.

*SaniGuard does not protect users or others against disease-causing bacteria.

Accessories (Sold Separately)

See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.





Compliance & Certifications



This space for Architect/Engineer Approval