

► Code Number

12001010

► Description

Complete system with exposed manual Sloan® urinal Flushometer and vitreous china retrofit urinal.

► Flush Cycle

0.125 gpf/0.5 Lpf

► Flushometer Specification

- Quiet, diaphragm type, chrome plated closet Flushometer and vitreous china water closet with the following features:
- PERMEX® Synthetic Rubber Diaphragm with twin linear filtered bypass and vortex cleansing action
- Free spinning Vandal Resistant Stop Cap and Adjustable Tailpiece
- 3/4" I.P.S. Screwdriver Bak-chek® angle Stop
- Spud coupling and flange for 3/4" top Spud
- Stop seat and vacuum breaker to be molded from PERMEX® rubber compound for chloramine resistance
- Compliant with the Buy American Act when purchased as a combination
- High Back Pressure vacuum breaker flush connection with one-piece bottom hex coupling nut
- High copper, low zinc brass castings for dezincification resistance
- Sweat Solder Adapter w/Cover Tube and Cast Wall Flange with Set Screw

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037/ ASME A112.19.2/CSA B45.1

► Fixture Specification




- Integral flushing rim
- Wall hung vitreous china
- Wash down flushing action
- All mounting hardware included
- Carrier Not Included
- Vandal resistant strainer assembly included
- 3/4" I.P.S. top spud inlet
- 2" NPT outlet flange
- Compliant to the applicable sections of ASME A112.19.2/CSA B45.1
- 100% factory flush tested

► Plumbing System Requirements

- Minimum Operating Flow Rate: 18 GPM
- Maximum Static Pressure: 80 PSI
- Minimum Flowing Pressure: 25 PSI

All information contained within this document subject to change without notice.

NOTE: All vitreous china dimensions shown in these drawings are nominal and not to scale. Dimensions can vary within the tolerances established in the governing ASME A112.19.2/CSA B45.1 standard. It is important to consider this when planning rough-in and plumbing layouts.



► Compliance & Certifications

CEC Compliant



CALGreen

This space for Architect/Engineer Approval