

## OPTIONS

### Flush Volume

- 1.6 gpf (6.0 Lpf) (1.6)
- 1.28 gpf (4.8 Lpf) (1.28)
- 3.5 gpf (13.2 Lpf) (3.5)

### Wall Plate Finish

- Stainless Steel (BSS)
- Polished Chrome (CP)

### Water Efficiency

- Low Consumption
- High Efficiency
- Water Saver

### Bypass

- Dual-Filtered Fixed Bypass Diaphragm (DFB)

### L Dimension

- 2"-10 3/4" (51-273mm) (2-10-3/4-LDIM)
- 13"-14 3/4" (330-375mm) (13-14-3/4-LDIM)
- 11"-12 3/4" (279-324mm) (11-12-3/4-LDIM)

### Override

- Electrical (OR)
- True Mechanical (TMO)

### Wall Box

- Front Accessible
- Small (SWB)
- With (W/BOX)
- Standard (not included, order separately)

### Control Stop

- Less (L/STOP)

### Compliances & Certifications

- BAA Compliant
- UL Certified
- ADA Compliant
- cUPC Certified
- BREEAM Water Credit
- Green Globes Water Credit
- CalGreen Compliant
- LEED V4 Water Efficiency Credit
- WaterSense Listed
- cUPC Green Certified

## NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change



## DESCRIPTION

Sloan® Concealed Sensor Flushometer

## FEATURES

- Flush volumes start as low as 1.6 gpf/6.0 Lpf;
- Water conservation is aided by the ADA-compliant, non-hold-open handle;
- Flush accuracy is controlled by CID™ technology, also enhancing water efficiency;
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance;
- Adjustable tailpiece to accommodate different height requirements.
- High chloramine resistant PERMEX synthetic rubber diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

## DOWNLOADS

- [Sloan 152/195 ESS TMO Installation Instructions](#)
- [Sloan Concealed Installation Instructions](#)
- [Sloan Concealed Spanish Installation Instructions](#)
- [Sloan/Regal ESS Repair and Maintenance Guide](#)
- [Additional Downloads](#)

## VIDEOS

-  ESS Flushometer

without notice.