Part No: CG-3632-030C Marine EverTUFF® CPVC True Union Ball Valve

Schedule 40 & 80

Desc: 3 CPVC MARINE TU2K STANDARD BV SOC FKM

MSRP: 972.81 Part Code: 179


Weight(lbs): 8.283 Weight(kg): 3.757 Weight(gm): 3757
Size: 3" Color: GRAY Material: CPVC

Type TU 2000 - Standard

O-Ring FKM

Connection Socket

Pressure Rating 150 psi @ 73° F



A = 6 - 3/16

 $\mathbf{B} = 7-1/16$

C = 10-13/16

 $\mathbf{D} = 5-1/2$

E = 7-5/8

 $\mathbf{Cv} = 1416$ **Values**

Injection Molded Dimension References:

G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses; $\pm 1/32$

H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; $\pm 1/32$ inch.

J = Intersection of center lines to bottom of socket/thread; 45° elbows; $\pm 1/32$ inch


L = Overall length of fittings; $\pm 1/16$ inch.


M = Outside diameter of socket/thread hub; $\pm 1/16$ inch.


N = Socket bottom to socket bottom; couplings; $\pm 1/16$ inch.


W = Height of cap; $\pm 1/16$ inch

Typical Molded Dimension References









The information printed here is based on current information & product design at the time of publication and is subject to change without notification. Spears® ongoing commitment to product improvement may result in some variation. No representation, guarantees or warranties of any kind are as to its accuracy, suitability for particular application or results to be obtained thereform. For verification of technical data or additional information, please contact Spears® Technical Service Department :: WEST COAST : (818) 364-1611 - EAST COAST : (717) 938-9006