Spears® Technical Information


Part No: 3776-663 **Fabricated DWV Double Wve**

Desc: 12X3 PVC RED DBL-WYE SOC SCH40 N.P.R.

MSRP: 518.09 Part Code: 390

Weight(kg): 10.4 Weight(lbs): 22.928 Weight(gm): 10400 Size: 12"X12"X3"X3" Color: WHITE **Material:** PVC

Schedule SCH 40 DWV



Reducing Type Connection Socket x Socket x Socket

G2 = 12-3/8

G3 = 13-11/16

H2 = 18-5/8

H3 = 15-15/16

L = 24-1/2

M = 13-9/16

M1 = 3-15/16

H1 = 5-7/8

Fabricated Dimension References:

(LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses; $\pm 1/4$ & larger $\pm 1/2$ inch.

Intersection of center lines to face of fitting; 90° elbows, tees, crosses; $\pm 1/4$ inch.; wyes $\pm 1/2$ inch; 14'' & larger

J = Intersection of center lines to bottom of socket/thread; 45° elbows; $\pm 1/4$ inch; 14° & larger $\pm 1/2$ inch.


L = Overall length of fittings; $\pm 1/2$ inch; wyes ± 1 inch; 14" & larger ± 1 inch.


 $M = Outside diameter of socket/thread hub; <math>\pm 1/4$ inch.


N = Socket bottom to socket bottom; couplings; $\pm 1/2$ inch.


 $W = \text{Height of cap}; \pm 1/4 \text{ inch.}$

Typical Fabricated Dimension References









The information printed here is based on current information & product design at the time of publication and is subject to change without notification. Spears® ongoing commitment to product improvement may result in some variation. No representation, guarantees or warranties of any kind are as to its accuracy, suitability for particular application or results to be obtained thereform. For verification of technical data or additional information, please contact Spears® Technical Service Department :: WEST COAST : (818) 364-1611 -EAST COAST: (717) 938-9006