## **Spears® Technical Information**

30-Aug-21 09:55:42 PM

**Fabricated Fittings** 

Desc: 12X2-1/2 CPVC RED DBL-WYE SOC S80 FAB G

**MSRP:** 5846.57 **Part Code:** 097


Weight(lbs): 42.036 Weight(kg): 19.067 Weight(gm): 19067
Size: 12"X2-1/2" Color: GRAY Material: CPVC

Schedule SCH 80

Connection Socket X Socket X Socket X

Socket

Type Reduction



G = 15/16

G2 = 11-13/16

H = 5-5/16

**Double Wve** 

H1 = 15-5/8

H2 = 18 - 1/16

Part No: 876-662CF

L = 23-3/8

M = 14-1/8

M1 = 3-7/16

111 13

## **Fabricated Dimension References:**

G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread;  $90^{\circ}$  elbows, tees, crosses;  $\pm 1/4$  & larger  $\pm 1/2$  inch.

H = Intersection of center lines to face of fitting;  $90^{\circ}$  elbows, tees, crosses;  $\pm 1/4$  inch.; wyes  $\pm 1/2$  inch; 14" & larger inch.

J = Intersection of center lines to bottom of socket/thread;  $45^{\circ}$  elbows;  $\pm 1/4$  inch;  $14^{\circ}$  & larger  $\pm 1/2$  inch.


L = Overall length of fittings;  $\pm 1/2$  inch; wyes  $\pm 1$  inch; 14" & larger  $\pm 1$  inch.


 $M = Outside diameter of socket/thread hub; <math>\pm 1/4$  inch.


N = Socket bottom to socket bottom; couplings;  $\pm 1/2$  inch.


 $W = \text{Height of cap}; \pm 1/4 \text{ inch.}$ 

## **Typical Fabricated Dimension References**









The information printed here is based on current information & product design at the time of publication and is subject to change without notification. Spears® ongoing commitment to product improvement may result in some variation. No representation, guarantees or warranties of any kind are as to its accuracy, suitability for particular application or results to be obtained thereform. For verification of technical data or additional information, please contact Spears® Technical Service Department :: WEST COAST : (818) 364-1611 - EAST COAST : (717) 938-9006