Spears® Technical Information

Part No: 801-910F Fabricated Fittings Tees

Desc: 24X10 PVC RED TEE SOC SCH80 FAB


MSRP: 8155.11 Part Code: 083

Weight(lbs): 236.578 Weight(kg): 107.31 Weight(gm): 107310 Size: 24"X24"X10" Color: GRAY Material: PVC

Schedule Schedule 80

Connection Socket X Socket X Socket

Type Reduction



G = 11 - 1/4

G1 = 15-15/16

G2 = 11 - 1/4

H = 23 - 1/4

H1 = 21-3/16

H2 = 23 - 1/4

 $\mathbf{L} = 46 \text{-} 1/2$

M = 26-7/16

M1 = 11-15/16

M2 = 26-7/16

Fabricated Dimension References:

G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses; $\pm 1/4$ & larger $\pm 1/2$ inch.

H = Intersection of center lines to face of fitting; 90° elbows, tees, crosses; $\pm 1/4$ inch.; wyes $\pm 1/2$ inch; 14" & larger

J = Intersection of center lines to bottom of socket/thread; 45° elbows; $\pm 1/4$ inch; 14° & larger $\pm 1/2$ inch.


L = Overall length of fittings; $\pm 1/2$ inch; wyes ± 1 inch; 14" & larger ± 1 inch.


 $M = Outside diameter of socket/thread hub; <math>\pm 1/4$ inch.


N = Socket bottom to socket bottom; couplings; $\pm 1/2$ inch.


 $W = \text{Height of cap}; \pm 1/4 \text{ inch.}$

Typical Fabricated Dimension References









The information printed here is based on current information & product design at the time of publication and is subject to change without notification. Spears® ongoing commitment to product improvement may result in some variation. No representation, guarantees or warranties of any kind are as to its accuracy, suitability for particular application or results to be obtained thereform. For verification of technical data or additional information, please contact Spears® Technical Service Department :: WEST COAST : (818) 364-1611 - EAST COAST : (717) 938-9006