Spears® Technical Information

Desc: 12X10 PVC RED DBL WYE SOC 100PSI SCH40 G

14-Sep-21 03:25:16 AM

Part No: 476-670F Fabricated Fittings Double Wve

MSRP: 2474.27 Part Code: 047

Weight(lbs): 67.946 Weight(kg): 30.82 Weight(gm): 30820


Size: 12"X10" Color: WHITE Material: PVC

> Schedule SCH 40

Socket X Socket X Socket X Connection

Socket

Type Reduction



G = 5-3/8G1 = 18 - 1/8

G2 = 18 - 1/8

H = 11-5/8

H1 = 23-3/8

H2 = 24-3/8

L = 36 $\mathbf{M} = 13 - 9/16$ M1 = 11 - 1/2

Fabricated Dimension References:

(LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses; $\pm 1/4$ & larger $\pm 1/2$ inch.

Intersection of center lines to face of fitting; 90° elbows, tees, crosses; $\pm 1/4$ inch.; wyes $\pm 1/2$ inch; 14" & larger

= Intersection of center lines to bottom of socket/thread; 45° elbows; $\pm 1/4$ inch; 14'' & larger $\pm 1/2$ inch.


L = Overall length of fittings; $\pm 1/2$ inch; wyes ± 1 inch; 14" & larger ± 1 inch.


 $M = Outside diameter of socket/thread hub; <math>\pm 1/4$ inch.


N = Socket bottom to socket bottom; couplings; $\pm 1/2$ inch.


 $W = \text{Height of cap}; \pm 1/4 \text{ inch.}$

Typical Fabricated Dimension References









The information printed here is based on current information & product design at the time of publication and is subject to change without notification. Spears® ongoing commitment to product improvement may result in some variation. No representation, guarantees or warranties of any kind are as to its accuracy, suitability for particular application or results to be obtained thereform. For verification of technical data or additional information, please contact Spears® Technical Service Department :: WEST COAST : (818) 364-1611 -EAST COAST: (717) 938-9006