



Manual Concealed Flushometer for Floor Mount or Wall Hung Water Closets, Concealed Rear Spud



*Compliances may change based on options selected.

Features

- Non-hold-open oscillating handle, Bak-Chek™ control stop and self-cleaning Xpelor Metering By-Pass ensure reliable operation and accurate flush delivery
- Available with adjustable or ground joint supply stop (ground joint recommended for salt water applications)
- Factory set flush volume of either 1.6 gpf/6.0 Lpf or 3.5 gpf/13.2 Lpf with adjustment range of 1.5 gpf/5.7 Lpf to 7.0 gpf/26.5 Lpf
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

Finishes

- Rough Brass

Flush Volume

- 1.6 gpf for Toilet
- 3.5 gpf for Toilet

Variations

- TP - Trap Primer
- E - Straight Stop Variation
- K - Wheel Handle Stop Variation
- GJ - Ground Joint Stop
- YO - Angle Stop Bumper
- YG - Angle Stop Extended Bumper
- YH - Single Wall Bumper
- YI - Double Wall Bumper
- FW - Fixture Wall Actuator
- HL - 3" Push Button, Front of Valve
- J - Metal Osculating Handle
- L - 3" Push Button
- MBFW - Metal Button, Fixture Wall
- MBPM - Metal Button, Panel Mount
- MP - Metal Partition Actuator
- SW - Side Wall Actuator
- YJ - Split Ring Pipe Support
- YK - Solid Ring Pipe Support
- YL - Split Ring with Seat Bumper Pipe Support
- XYV - Valve Less Vacuum Breaker
- O - Offset Vacuum Breaker
- 1" Flush Connection
- W - 3/4 inch Flush Connection
- H - Handle on front
- WWT - Whitworth Thread
- C - Inlet on Left Side of Valve