

CODE NUMBER

3365345BT

DESCRIPTION

Plug Adapter Power Supply, Below Deck Manual Mixing Valve, Polished Chrome Finish, 2.2 gpm, Laminar Spray, Infrared Sensor, Smart Faucet, Optima® Hardwired-Powered Wall-Mounted Gooseneck Body Faucet.

DETAILS

• Flow Rate: 2.2 gpm (8 Lpm) (2.2GPM)

Spray Type: Laminar (LAM)
Spout Type: Surgical Bend (S)
Sensor Type: Infrared (IR)
Mounting Type: Single Hole
Power Supply: Plug Adapter (PLG)

• Temperature Mixer: Below Deck Manual Mixing Valve (BDM)

Finish: Polished Chrome (CP)
Factory Default Timeout: 30s
Factory Default GPC: 1.1

FEATURES

Commercial Grade Faucet, ADA Compliant, Cast Brass Spout, Quick Connect Fittings, Integrated Water Shut-off, Wireless Settings Adjustment, On-demand or Metered activation, Hygienic Line Flush, Water Usage and Battery Strength Reporting, Self-adapting Sensor

ELECTRICAL SPECIFICATIONS

Battery Life: 3 years 8,000 cycles/month
 Optional power harvesting significantly extends service life

Self-Adjustment Range: 0" (0mm)Sensor Range: 0" (0mm)

• Timeout Adjustment Settings: 30s

POWER SUPPLY OPTIONS

• 6VDC Plug Adapter (included with PLG models)

• 6VDC Ganged Adapter Kit (up to 6 units)(sold separately)

• 24VAC Box Transformer (included with BOX models)

VIDEOS


Optima Faucet App



DOWNLOADS

- Optima Smart Faucet Below Deck Installation Instructions
- Trim Plates Repair and Maintenance Guide
- Faucet Spray Heads Repair and Maintenance Guide
- ETF-500/500-S and EBF-550/550-S Below Deck Repair and Maintenance Guide
- Additional Downloads





COMPLIANCES & CERTIFICATIONS



ASME











(ADA Compliant, ASME A112.18.1 Compliant, cUPC Certified, cUPC Low Lead Compliant, Proposition 65, TAS, UL Certified, UPC Certified, UPC Low Lead Compliant)

RECOMMENDED SPECIFICATION

Faucet shall include cast brass body, quick-connect fittings, twist-off/shut-off solenoid assembly, removable battery cartridge, flexible power supply and allow adjustment of settings wirelessly via Apple or Android smartphones.

NOTES

All information contained within this document subject to change without notice.




Looking for other variations of the ETF-500 product? View the general spec sheet with all options.


Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.


WARRANTY

3 Year

ROUGH-IN







Double Inlet Filter Fitting

Single Inlet Filter Fitting Kit with Below Deck Manual Mixing Valve (BDM)

Single Inlet Filter Fitting Kit with Below Deck Thermostatic Mixing Valve (BDT)

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com