Spears® Technical Information

16-Sep-21 09:47:18 PM

Part No: 3776-624 Fabricated DWV

Desc: 10X4 PVC RD DBL-Y SOC SCH40 N.P.R.

MSRP: 406.56 Part Code: 390


Weight(lbs): 18.843 Weight(kg): 8.547 Weight(gm): 8547
Size: 10"X10"X4"X4" Color: WHITE Material: PVC

Schedule SCH 40 DWV

Type Reducing

Connection Socket x Socket x Socket x Socket

Double Wve



G1 = 1-7/16

G2 = 12-3/16

G3 = 13-5/16

H1 = 6-11/16

H2 = 17-7/16

H3 = 15-9/16

 $\mathbf{L} = 24\text{-}1/8$

M = 11-1/2

 $\mathbf{M1} = 5$

Fabricated Dimension References:

G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses; $\pm 1/4$ & larger $\pm 1/2$ inch.

H = Intersection of center lines to face of fitting; 90° elbows, tees, crosses; $\pm 1/4$ inch.; wyes $\pm 1/2$ inch; 14" & larger inch.

J = Intersection of center lines to bottom of socket/thread; 45° elbows; $\pm 1/4$ inch; 14° & larger $\pm 1/2$ inch.


L = Overall length of fittings; $\pm 1/2$ inch; wyes ± 1 inch; 14" & larger ± 1 inch.

 $M = Outside diameter of socket/thread hub; <math>\pm 1/4$ inch.


N = Socket bottom to socket bottom; couplings; $\pm 1/2$ inch.


 $W = \text{Height of cap}; \pm 1/4 \text{ inch.}$


Typical Fabricated Dimension References



EAST COAST: (717) 938-9006







The information printed here is based on current information & product design at the time of publication and is subject to change without notification. Spears® ongoing commitment to product improvement may result in some variation. No representation, guarantees or warranties of any kind are as to its accuracy, suitability for particular application or results to be obtained thereform. For verification of technical data or additional information, please contact Spears® Technical Service Department :: WEST COAST : (818) 364-1611 -