SLV-3020

SPEAKMAN®

Sentinel Mark II® Vandal Resistant Shower Combination (Valve not included)

FEATURES:

CPT-3001: Shower Valve Trim

• S-2280: Vandal Resistant Wall-Mounted Shower Head



VALVE OPTIONS:

• CPV-PB: Pressure Balance Valve
Sweat & Thread Connections

• CPV-PB-PXC: Pressure Balance Valve
PEX F1807 Crimp Inlet Connections

• CPV-PB-PXE: Pressure Balance Valve
PEX F1960 Cold-Expansion Inlet Connections

• CPV-T: Thermostatic Valve
Sweat & Thread Connections

•CPV-T-PXC: Thermostatic Valve
PEX F1807 Crimp Inlet Connections

•CPV-T-PXE: Thermostatic Valve
PEX F1960 Cold-Expansion Inlet Connections



STOCK FINISHES:



PC

STANDARDS:

• ASME A112.18.1/CSA B125.1 certified

WARRANTY:

Visit www.speakman.com for full product warranty information

• See Speakman.com For Warranty Information

Information continues on next page


Architect/Engineer Approval Space:

P: 800-537-2107
F: 800-977-2747
W: WWW.SPEAKMAN.COM
R: 01-JANUARY 2019

SLV-3020

SPEAKMAN®

Sentinel Mark II® Vandal Resistant Shower Combination (Valve not included)



NOTES:

1. ALL DIMENSIONS ARE IN INCHES [MILLIMETERS] UNLESS OTHERWISE SPECIFIED AND ARE SUBJECT TO CHANGE WITHOUT NOTICE.
2. ALL INLETS AND OUTLETS ARE 1/2" FEMALE COPPER SWEAT AND 1/2" MALE NPT UNLESS OTHERWISE SPECIFIED.
3. FOR ADA MOUNTING LOCATIONS CONSULT ADAAG, ANSI A117.1, OR STATE REGULATIONS.

DIMENSION	CPV-PB	CPV-T	CPV-PB-PXC	CPV-PB-PXE	CPV-T-PXC	CPV-T-PXE
A	7/16" (11mm)	1/2" (12mm)	7/16" (11mm)		1/2" (12mm)	
B	3-5/16" (84mm)	3-1/2" (89mm)	3-5/16" (84mm)		3-1/2" (89mm)	
C	4-13/16" (123mm)	5-7/8" (150mm)	4-13/16" (123mm)		5-7/8" (150mm)	
D	2-1/2" (63mm) MIN TO 3-1/2" (89mm) MAX					
E			3-1/8" (79mm) MIN TO 4-1/8" (105mm) MAX		3-3/16" (81mm) MIN TO 4-3/16" (106mm) MAX	

Architect/Engineer Approval Space:

P: 800-537-2107
F: 800-977-2747
W: WWW.SPEAKMAN.COM

R: 01-JANUARY 2019