SLV-3030

SPEAKMAN®

Sentinel Mark II® Trim, Shower and Tub Combination (Valve not included)

FEATURES:

- CPT-3001: Shower Valve Trim
- S-2272-E2: Shower Head 2.0 GPM (7.6 L/min) flow rate
- S-2500: Shower Arm & Flange
- S-1556: Diverter Tub Spout

VALVE OPTIONS:

- CPV-PB: Pressure Balance Valve
  Sweat & Thread Connections
- CPV-PB-PXC: Pressure Balance Valve
  PEX F1807 Crimp Inlet Connections
- CPV-PB-PXE: Pressure Balance Valve
  PEX F1960 Cold-Expansion Inlet Connections
- CPV-T: Thermostatic Valve
  Sweat & Thread Connections
- •CPV-T-PXC: Thermostatic Valve
  PEX F1807 Crimp Inlet Connections
- CPV-T-PXE: Thermostatic Valve
  PEX F1960 Cold-Expansion Inlet Connections

STOCK FINISHES:



PC

STANDARDS:

- ASME A112.18.1/CSA B125.1 certified
- WaterSense certified

WARRANTY:

Visit www.speakman.com for full product warranty information

- See Speakman.com For Warranty Information







Information continues on next page

Architect/Engineer Approval Space:

P: 800-537-2107
F: 800-977-2747
W: WWW.SPEAKMAN.COM
R: 01-JANUARY 2019

Sentinel Mark II® Trim, Shower and Tub Combination (Valve not included)



NOTES:

1. ALL DIMENSIONS ARE IN INCHES [MILLIMETERS] UNLESS OTHERWISE SPECIFIED AND ARE SUBJECT TO CHANGE WITHOUT NOTICE.
2. ALL INLETS AND OUTLETS ARE 1/2" FEMALE COPPER SWEAT AND 1/2" MALE NPT UNLESS OTHERWISE SPECIFIED.
3. FOR ADA MOUNTING LOCATIONS CONSULT ADAAG, ANSI A117.1, OR STATE REGULATIONS.

DIMENSION	CPV-PB	CPV-T	CPV-PB-PXC	CPV-PB-PXE	CPV-T-PXC	CPV-T-PXE
A	7/16" (11mm)	1/2" (12mm)	7/16" (11mm)		1/2" (12mm)	
B	3-5/16" (84mm)	3-1/2" (89mm)	3-5/16" (84mm)		3-1/2" (89mm)	
C	4-13/16" (123mm)	5-7/8" (150mm)	4-13/16" (123mm)		5-7/8" (150mm)	
D	2-1/2" (63mm) MIN TO 3-1/2" (89mm) MAX					
E			3-1/8" (79mm) MIN TO 4-1/8" (105mm) MAX		3-3/16" (81mm) MIN TO 4-3/16" (106mm) MAX	

Architect/Engineer Approval Space:

P: 800-537-2107
F: 800-977-2747
W: WWW.SPEAKMAN.COM
R: 01-JANUARY 2019