**U.S. Tsubaki Power Transmission, LLC**
301 E. Marquardt Dr.
Wheeling, IL 60090

**Phone:** 847.459.9500 or 800.323.7790
**Fax:** 847.459.9515

**Email:** sales@ustsubaki.com
**Website:** www.ustsubaki.com



# ITEM # BS85-3D, BS85-3 1/4" BORE CAM CLUTCH

BS Series Cam Clutch products are designed to provide inner race overrunning capability in one direction of operation, and engage the outer race when reverse rotation is experienced. BS Series units are often found on incline conveyor systems, or pump systems that may experience reverse rotation due to excessive loading on the discharge side of the pump. BS Series Cam Clutches are a cam and roller design incorporating the low friction bearing into the cam cage.

A complete Cam Clutch assembly

more




| Specifications | |
|---|---|
| Torque | 4336.9 lb·ft<br>5880.0 N·m |
| Inner Race Max. Overrunning Speed | 300 rpm |

| | |
|---|---|
| Drag Torque | 5.782 lb·ft<br>7.84 N·m |
| A (Overall Length) | 4.528 in<br>115.00 mm |
| B (Diameter) | 8.268 in<br>210.00 mm |
| C (Inside Width) | 4.331 in<br>110.00 mm |
| D (Bolt Circle Diameter) | 7.283 in<br>185.00 mm |
| E (Inner Race O.D.) | 4.528 in<br>115.00 mm |
| S (Thread Depth) | 1.181 in<br>30.00 mm |
| H-M (Size x Pitch No. of Tapped Holes, Qt.) | M12 x P1.75 (6) |
| Weight (Approx.) | 59.840 lb<br>27.200 kg |