U.S. Tsubaki Power Transmission, LLC
301 E. Marquardt Dr.
Wheeling, IL 60090


Phone: 847.459.9500 or 800.323.7790
Fax: 847.459.9515
Email: sales@ustsubaki.com

Website: www.ustsubaki.com

ITEM # BR40HT-R66B-45, BR-HT40-45.00 MM BORE CAM CLUTCH

BR-HT is mainly used in backstop applications as an integral part of a gear reducer. Prevention of reverse rotation for inclined conveyor and bucket elevator are typical application BR-HT assures not only the immediate backstop function under high torque, but also long service life by the “lift-off” design. In addition, installation on the high speed shaft with low torque enables selection of more compact models with resulting lower cost.





Specifications

Torque	626.9 lb·ft 850.0 N·m
Min. Inner Race Overrunning Speed	670 rpm
Max. Inner Race Overrunning Speed	3600 rpm
Max. Engagement	320 rpm
Bore Size	1.772 in 45.00 mm

A (Inner Race Width)	1.378 in 35.00 mm
B (Outer Race Width)	1.378 in 35.00 mm
C (Outer Race O.D.)	5.197 in 132.00 mm
D (Outer Race I.D.)	3.543 in 90.00 mm
E (Inner Race O.D.)	2.559 in 65.00 mm
G (Bolt Circle Diameter)	4.528 in 115.00 mm
Q-R (Mounting Holes Quantity - Size)	8-M8
S-T (Removed Holes Quantity - Size)	2-M8
F (Cam Width)	0.984 in 25.00 mm
Weight	6.380 lb 2.900 kg
H (Housing Bore Min.)	3.228 in 82.00 mm
M (Counter Bore Depth Max.)	0.157 in 4.00 mm
N (Chamfer)	0.039 in 1.00 mm