

## Veritek<sup>®</sup> NEO Angle Shower Floors With Fit-Flo™ Drain

### Manufactured from Veritek®

(See page 2 for detailed information.)

WARRANTY

Limited Lifetime – Residential


Limited 5-year – Commercial


#### **FEATURES**

- Will not mold or mildew, no grout to clean.
- Coordinates with other Swanstone or Veritek® products.
- Pebbled, slip-resistant surface.
- Made of Veritek® with no surface coating to chip or crack.

|         | Nominal   | Rough-In Dimensions |          |         |          |  |
|---------|-----------|---------------------|----------|---------|----------|--|
| Model   | Size      | Α                   | В        | 25"     | 12"      |  |
| R-36NEO | 36" x 36" | 36-1/8"             | 18-3/16" | 25-1/8" | 12-3/16" |  |
| R-38NEO | 38" x 38" | 38-1/8"             | 20-3/16" | 25-1/8" | 12-3/16" |  |

IMPORTANT: Rough-in dimensions are provided for reference only. You must measure the actual shower floor and check local building code requirements before construction of the stud wall.





#### **SPECIFICATIONS**

## Veritek<sup>®</sup> NEO Angle Shower Floors With Fit-Flo™ Drain

|         |           |                                    | Ship    | Ship  | Carton       |         |
|---------|-----------|------------------------------------|---------|-------|--------------|---------|
| Model   | Part      | Nominal Size Dimensions            | Wt. Lb. | FedEx | Dims. In.    | Cu. Ft. |
| R-36NEO | FNooo36MD | 36" D x 36" W<br>(914 mm x 914 mm) | 40      | -     | 42 X 42 X 10 | 11      |
| R-38NEO | FNooo38MD | 38" D x 38" W<br>(965 mm x 965 mm) | 44      | -     | 44 X 43 X 10 | 11      |

Includes: One code-approved compression-molded Veritek  $^{\tiny \circledcirc}$  shower floor with molded-in Fit-Flo drain.

Packaging: Each floor packed in a rectangular carton.

## **COLORS**

#### **Solid Colors:**

- White (010)
- Bisque (018)
- Bone (037)

#### STANDARDS AND RATINGS

American National Standard Institute—ANSI Z124.1.2 International Association of Plumbing and Mechanical Officials (IAPMO)—Listed CSA Standard B45.5 by IAPMO Uniform Plumbing Code (UPC)

For a complete list of tests and results see the Technical Data Sheet.

#### SUPPORT DOCUMENTS

Installation instructions available at swanstone.com.

# MADE IN USA

# MAINTENANCE AND CLEANING INFORMATION

Clean regularly with common household liquid cleaners and a sponge or soft cloth. For hard water stains, scale removers can be used. If necessary, abrasive cleaners can be used with a nylon brush or pad to remove build up on the shower floor surface. **Do not** use a metal-scouring pad or a wire brush, as it will damage the surface. **Do not** use "leave on" cleaning products, such as automatic spray shower cleaners. Prolonged contact with harsh chemicals could have an adverse reaction over time and discolor surfaces. **Do not** use cleaning agents that caution use on acrylic, polyester or plastics.