



LED STRIP LUMINAIRE | **BASIC**

EVERLINE



* Shown with
lens accessory
purchased
separately

Reliable Performance

Industry-Leading Reliability

Universal's LED Strip Luminaire is a simple indoor, suspended, strip lighting fixture. These products can reduce energy and increase your workspace productivity. This fixture is a good choice for new and retrofit lighting projects.

Features & Benefits:

- 2', 4', 8' Options
- Energy Efficient:
 - Up to 50% more efficient than fluorescent technology
 - 0-10V Dimming Standard
 - Save even more energy with optional occupancy or daylight sensors
- Easy Maintenance & Installation:
 - Lumen Maintenance exceeds L70 at 60,000 hours
- Potential for rebates
- No Mercury. Save on costly lamp recycling and/or hazardous waste disposal
- High-reflectance baked enamel finish
- End plate doubles as a coupler or alignment device for continuous row mounting

Applications:

- Surface Mount or Chain Mount
- Mount individually or in a continuous row
- Indoor, non-condensing, non-corrosive environments
- 120-277V
- Ideal for: Stairwells, Corridors, Light Industrial and Back of House Applications



For a list of DesignLights Consortium® QPL listed products please visit www.designlights.org/qpl/en/saved/UBU24XJ




5 YEAR WARRANTY

Industry-Leading Reliability

For 70 years, Universal has been on the cutting edge of high efficiency lighting design, pushing the industry towards increasingly higher standards of energy efficiency for LED systems, lighting ballasts, and control systems.

"Matched Systems"

Universal makes it easy to upgrade to LED technology with our complete in-house design (electronic, thermal and optical) including EVERLINE® "matched" modules and drivers.



Controllability

Optional OS PIR motion detector turns light on when occupancy is detected and turns light off, after a time delay, when no occupancy is detected. Comes with two interchangeable lenses for use at different mounting heights from 8 to 40 ft.

For even more control, optional ODS Internal photocell dims luminaire and reduces power consumption when adequate natural light is present.

PACKAGED DIMENSIONS (in)				
Format	L	W	H	lb
24 in	25	5.25	2.50	4
48 in	49	5.25	2.50	8
96 in	97	5.25	2.50	16

Nominal Dimensions

PRODUCT ENVELOPE (in)			
Format	L	W	H
24 in	24	4.25	2.00
48 in	48	4.25	2.00
96 in	96	4.25	2.00

Nominal Dimensions

Options:

- Lens plate for optional lens
- 6 Ft, 3 Wire whip
- 6 Ft Cord set
- 10 watt Battery Pack option delivers approximately 1200 lumens for 90 minutes.
- PIR on/off occupancy sensor
- PIR occupancy & photo sensor with on/off & dimming control

Consistent Illumination:

- Color Temperatures (CCTs) of 3000K, 3500K, 4000K and 5000K
- Not vulnerable to color and intensity aberrations associated with routine lamp maintenance of fluorescent systems.

Performance:

Fixture	Watts	Lumens	LPW
24 in	18.6	2,590	139
	24	3,355	140
	28	3,705	132
48 in	24	3,475	145
	35	4,920	141
	48	6,475	135
	59	7,755	131
96 in.	48	6,475	135
	70	9,840	141
	97	12,950	134
	118	15,510	131

Product Ordering Information:

Ordering Information

Series	Format	-	Watts	W	CRI	Color Temp.	-	Voltage	-	Options
STRP4 = 4.25 Inch, Strip Style Luminaire	24 in	-	18 ¹ 24 ⁴ 28 ¹	W	8 = 80 (minimum)	30 = 3000K 35 = 3500K 40 = 4000K 50 = 5000K (Nominal)	-	U = 120-277 VAC 50/60 Hz	-	LNPL⁷ = Lens plates (longer end plates to accommodate a separately purchased lens) WP = 6 FT, 3 Wire, whip C6F⁶ = 6 FT cord set EM⁵ = Backup battery pack OS = PIR on/off occupancy sensor ODS = PIR occupancy & photo sensor with on/off & dimming control
	48 in	-	24 ⁴ 35 ² 48 ⁵ 57 ²							
	96 in	-	48 ⁵ 70 ³ 97 ³ 114 ³							

ORDERING NOTES:

1. 24 inch length only
2. 48 inch length only
3. 96 inch length only
4. 24 & 48 inch lengths only
5. 48 & 96 inch lengths only
6. For use on 120VAC systems only
7. Fixtures with the LNPL option do not come equipped with standard end plates (which can be used for alignment). For continuous row mounting of fixtures with lenses, order standard fixtures, matching lenses (see above) and as many STRP4-ACC-LNPL accessories (see above) as needed to finish the rows.

ACCESSORIES

STRP4-ACC-WG4	4-Ft Wire guard	STRP4-ACC-LEN8	8-Ft Lens	STRP4-ACC-LNPL	2pc End plate for use with lens
STRP4-ACC-LEN2	2-Ft Lens	STRP4-ACC-PNDKIT	2ps V-Hook & 2pc 2-Ft Chain		
STRP4-ACC-LEN4	4-Ft Lens				



It's EASY to REACH US...

LIT#: SLF071718

UNIVERSAL LIGHTING TECHNOLOGIES, INC.
51 Century Blvd., Suite 230
Nashville, TN 37214-3683

GENERAL INFO: (615) 316-5100

For Technical Engineering Services (TES), application support and warranty information, call **1-800-225-5278**

WEBSITE: unvlt.com
EMAIL: webmaster@unvlt.com