

Valves and Accessories by Model

Model 2971.1ZL

Zero Lead Bronze Ball Valve - P x P

- Smart Connect Feature
- 250 CWP
- Body: Two Piece Zero Lead Bronze Body
- Ball: Full Port 316 Stainless Steel
- Stem: Blowout-Proof Eco Brass
- Sealing Element: EPDM
- Listings: NSF-61-372, U.P. Code, ASME A112.4.14
- Conforms to: MSS SP-110
- Parameters: 250 psi Maximum Working Pressure
0° - 250°F Operating Temperature

ZERO LEAD.



Part Number	Size
79920	1/2"
79925	3/4"
79930	1"
79935	1 1/4"

Model 2971.3ZL

Zero Lead Bronze Ball Valve - P x P

- Smart Connect Feature
- 250 CWP
- Body: Two Piece Zero Lead Bronze Body
- Ball: Full Port 316 Stainless Steel
- Stem: Blowout-Proof 316 Stainless Steel
- Sealing Element: EPDM
- Listings: NSF-61-372, U.P. Code, ASME A112.4.14
- Conforms to: MSS SP-110
- Parameters: 250 psi Maximum Working Pressure
0° - 250°F Operating Temperature

ZERO LEAD.



Part Number	Size
79923	1/2"
79928	3/4"
79933	1"
79938	1 1/4"

Model 2970.1ZL

Zero Lead Bronze Ball Valve - P x P

- Smart Connect Feature
- 250 CWP
- Body: Two Piece Zero Lead Bronze Body
- Ball: Full Port 316 Stainless Steel
- Stem: Blowout-Proof Eco Brass
- Sealing Element: EPDM
- Listings: NSF-61-372, U.P. Code, ASME A112.4.14
- Conforms to: MSS SP-110
- Parameters: 250 psi Maximum Working Pressure
0° - 250°F Operating Temperature



Part Number	Size
79115	1 1/2"
79120	2"

Model 2970.3ZL

Zero Lead Bronze Ball Valve - P x P

- Smart Connect Feature
- 250 CWP
- Body: Two Piece Zero Lead Bronze Body
- Ball: Full Port 316 Stainless Steel
- Stem: Blowout-Proof 316 Stainless Steel
- Sealing Element: EPDM
- Listings: NSF-61-372, U.P. Code, ASME A112.4.14
- Conforms to: MSS SP-110
- Parameters: 250 psi Maximum Working Pressure
0° - 250°F Operating Temperature



Part Number	Size
79840	1 1/2"
79845	2"

Model 2971.4ZL

Zero Lead Bronze Ball Valve - P x FPT

- Smart Connect Feature
- 250 CWP
- Body: Two Piece Zero Lead Bronze Body
- Ball: Full Port 316 Stainless Steel
- Stem: Blowout-Proof Eco Brass
- Sealing Element: EPDM
- Listings: NSF-61-372, U.P. Code, ASME A112.4.14
- Conforms to: MSS SP-110
- Parameters: 250 psi Maximum Working Pressure
0° - 250°F Operating Temperature

ZERO LEAD.



Part Number	Size
79970	1/2"
79975	3/4"
79980	1"

Model 2971.6ZL

Zero Lead Bronze Ball Valve - P x Hose

- Smart Connect Feature
- 250 CWP
- Body: Two Piece Zero Lead Bronze Body
- Ball: Full Port 316 Stainless Steel
- Stem: Blowout-Proof Eco Brass
- Sealing Element: EPDM
- Listings: NSF-61-372, U.P. Code, ASME A112.4.14
- Conforms to: MSS SP-110
- Parameters: 250 psi Maximum Working Pressure
0° - 250°F Operating Temperature

ZERO LEAD.



Part Number	Size
79875	1/2"
79876	3/4"

Model 2973

Bronze Ball Valve - P x P

- Smart Connect Feature
- 200 CWP
- Body: Brass Body with Bronze Connections
- Ball: Full Port Chrome Plated Brass
- Stem: Blowout-Proof Brass
- Sealing Element: EPDM
- Listings: U.P. Code, IAPMO IGC 157
- Conforms to: MSS SP-110
- Parameters: 200 psi Maximum Working Pressure
0° - 250°F Operating Temperature



Part Number	Size
24000	1/2"
24005	3/4"
24010	1"
24015	1 1/4"
24020	1 1/2"
24025	2"

Model 2973.1

Bronze Ball Valve - P x FPT

- Smart Connect Feature
- 200 CWP
- Body: Brass Body with Bronze Connections
- Ball: Full Port Chrome Plated Brass
- Stem: Blowout-Proof Brass
- Sealing Element: EPDM
- Listings: U.P. Code, IAPMO IGC 157
- Conforms to: MSS SP-110
- Parameters: 200 psi Maximum Working Pressure
0° - 250°F Operating Temperature



Part Number	Size
24030	1/2"
24035	3/4"
24040	1"

Valves and Accessories by Model

Model 2973.2

Bronze Ball Valve - P x Hose

- Smart Connect Feature
- 200 CWP
- Body: Brass Body with Bronze Connections
- Ball: Full Port Chrome Plated Brass
- Stem: Blowout-Proof Brass
- Sealing Element: EPDM
- Listings: U.P. Code, IAPMO IGC 157
- Conforms to: MSS SP-110
- Parameters: 200 psi Maximum Working Pressure
0° - 250°F Operating Temperature



Part Number	Size
24090	1/2"
24095	3/4"

Model 0670

Bronze Gas Ball Valve - P x P

- Smart Connect Feature
- 600 WOG
- Body: Two Piece Bronze Body
- Ball: Full Port Chrome Plated Brass
- Stem: Blowout-Proof Brass
- Sealing Element: HNBR
- Listings: CSA LC4
- Conforms to: IFGC NFPA 54
- Parameters: 125 psi Maximum Working Pressure
-40° - 180°F Operating Temperature



Part Number	Size
19648	1/2"
19653	3/4"
19658	1"
19663	1 1/4"
19668	1 1/2"
19673	2"

Model 4070

316 Stainless Steel Ball Valve - P x P

- Smart Connect Feature
- Body: 316 Stainless Steel
- Ball: 316 Stainless Steel Fullport
- Stem: Blow-out Proof 316 Stainless Steel
- Sealing Element: EPDM
- Listings: NSF-61-372
- Conforms to: MSS SP-110
- Parameters: 200 psi Maximum Working Pressure
0° - 250°F Operating Temperature



Part Number	Size
81080	1/2"
81085	3/4"
81090	1"
81095	1 1/4"
81100	1 1/2"
81105	2"

Model 4370.8

316 Stainless Steel Three Piece Ball Valve - P x P

- Smart Connect Feature
- Body: Three Piece 316 Stainless Steel
- Ball: 316 Stainless Steel Fullport
- Stem: Blow-out Proof 316 Stainless Steel
- Sealing Element: FKM
- Conforms to: MSS SP-110
- Parameters: 200 psi Maximum Working Pressure
0° - 250° Operating Temperature



Part Number	Size
85132	1/2"
85133	3/4"
85134	1"
85136	1 1/4"
85137	1 1/2"
85138	2"



Valves and Accessories by Model

Model 2974ZL Inline Check Valve

ZERO LEAD.

- Smart Connect Feature
- Body: Zero Lead Bronze
- Check Valve Insert: POM Bubble Tight
- Cracking Pressure: 0.5 PSIG
- Sealing Element: EPDM
- Listings: UPC NSF-61-372
- Parameters: 200 psi Maximum Working Pressure
0° - 180°F Operating Temperature



Part Number	Size
79035	1/2"
79040	3/4"
79045	1"
79050	1 1/4"
79055	1 1/2"
79060	2"

Model 2873.81 Semi Lug Butterfly Valve

- Body: Semi-Lug Spheroidal Cast Iron
- Disc: 316 Stainless Steel
- Stem: 316 Stainless Steel
- Handle: 10 Position Spring Locking Handle
- Mounting Flange: ISO 5211
- Liner: EPDM
- Conforms to: MSS SP 67, AWWA C504-6
- Parameters: 250 psi Maximum Working Pressure
0° - 200°F Operating Temperature



Part Number	Size
22074	2 1/2"
22075	3"
22076	4"

Valve Accessories by Model

Model 2971.8 Ball Valve Lockable Metal Handle

*Use with Models 2971ZL



Part Number	Size
22170	1/2" & 3/4"
22172	1" & 1 1/4"

Model 2971.96 Ball Valve Stem Extension Kit

*Use with Models 2971ZL



Part Number	Size
23443	1/2" & 3/4"
23445	1" & 1 1/4"
23447	1 1/2" & 2"

Model 2973.8 Ball Valve Metal Handle

*Use with Models 2973



Part Number	Size
22176	1/2"
22178	3/4" & 1"
22180	1 1/4" & 2"

Model 2973.96 Ball Valve Stem Extension Kit

*Use with Models 2973



Part Number	Size
23449	1/2"
23451	3/4" & 1"
23453	1 1/4" to 2"

Model 2970.8 Ball Valve Lockable Metal Handle

*Use with Model 4070 and 2970ZL



Part Number	Size
22143	1/2", 3/4", 1"
22163	1 1/4", 1 1/2", 2"

Model 2970.96 Ball Valve Stem Extension Kit

*Use with Model 4070 and 2970ZL



Part Number	Size
23442	1/2", 3/4", 1"
23444	1 1/4", 1 1/2", 2"

Model 2959.7 Flange Bolt Set

*Use with Model 2873.81



Part Number	Size
19748	1", 1 1/4", 1 1/2"
19758	2", 2 1/2", 3"
19763	4"

This document subject to updates. For the most current Viega technical literature please visit www.viega.us.
Click Services -> Click Electronic Literature Downloads -> Select Product Line -> Select Desired Document

Viega LLC, 100 N. Broadway, 6th Floor • Wichita, KS 67202 • Ph: 800-976-9819 • Fax: 316-425-7618