

For Residential and Light Commercial Applications

Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____

Contractor's P.O. No. _____

Approval _____

Representative _____

Series PWUV

Watts UV Disinfection Systems

Pipe Sizes: 1/2" – 1" (15 – 25mm)

Flow Rate: Up to 12 gpm (45 lpm)

Watts PWUV systems are manufactured from 304 stainless steel and have an audible and visual lamp failure alarm. They are durable and well constructed, yet economically priced.

Features

- Disinfection without chemicals
- Effective disinfection for chlorine resistant bacteria, virus and cysts
- Lamps rated for 12-month continuous service life
- Highly polished 304 stainless steel reactor chamber
- Audible and visual alarm indicating lamp failure
- Easy lamp replacement
- Available in 110v and 220V
- 30 mj/cm2 dose at specified flow rate at the end of lamp life

Applications

- Well water
- Homes
- Water systems
- Aquaculture
- Food service
- Water coolers
- RO systems

PURE WATER



PWUV

Note: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



Specifications

Chamber materials	304SS
Max. water temperature	104°F (40°C)
Min. water temperature	36°F (2°C)
Max pressure	125psi
UV dose (end of life)	30 mj/cm ²
Lamp life	9,000 hrs
Lamps per chamber	Single

Water Quality Guidelines

Total Iron	less than 0.3 mg/l
Hydrogen sulfide	less than 0.05 mg/l
Turbidity	less than 1.0 NTU
Manganese	less than 0.05 mg/l
Hardness	less than 7 grains
UV transmittance	greater than 90%

Note: Minimum water quality guidelines are recommended to ensure proper operation and continuous disinfection.

Models

MODEL NO.	FLOW RATE	PIPE SIZE	DIMENSIONS	ELECTRICAL	SHIPPING WEIGHT	
	(GPM)		(L X W X H)		lbs.	kgs.
PWUV2110	2	1/2" MNPT	18" x 6" x 5-3/8"	110-130 v / 50-60 Hz	6	3
PWUV2220	2	1/2" MNPT	18" x 6" x 5-3/8"	200-250 v / 50-60 Hz	6	3
PWUV6110	6	3/4" MNPT	25-1/2" x 6" x 5-3/8"	110-130 v / 50-60 Hz	7	3
PWUV6220	6	3/4" MNPT	25-1/2" x 6" x 5-3/8"	200-250 v / 50-60 Hz	7	3
PWUV8110	8	3/4" MNPT	32" x 8-1/4" x 3-3/4"	110-130 v / 50-60 Hz	9	4
PWUV8220	8	3/4" MNPT	32" x 8-1/4" x 3-3/4"	200-250 v / 50-60 Hz	9	4
PWUV12110	12	1" MNPT	41-1/2" x 8-1/4" x 3-3/4"	110-130 v / 50-60 Hz	17	8
PWUV12220	12	1" MNPT	41-1/2" x 8-1/4" x 3-3/4"	200-250 v / 50-60 Hz	17	8

Replacement Parts

FLOW RATE (GPM)	BULB MODEL	BALLAST MODEL	QUARTZ SLEEVE MODEL
2	PWUVBULB2	PWUVBAL2	PWUVQS2
6	PWUVBULB6	PWUVBAL6-12	PWUVQS6
8	PWUVBULB8	PWUVBAL6-12	PWUVQS8
12	PWUVBULB12	PWUVBAL6-12	PWUVQS12



A Watts Water Technologies Company



USA: Tel. (800) 224-1299 • www.watts.com
Canada: Tel. (888) 208-8927 • www.watts.ca