

INSTALLATION INSTRUCTIONS**Series 622UF/UFT****Union Ball Valves**

Sizes: 1/2" - 2" (15 – 50mm)

Installation Instructions

Kit Part No: 905573, 905574, 905575, 905576, 905577, & 905578
 Instruction #2 does not apply to Kit No. 905573

- 1) Unscrew the union connection and remove old O-ring.
- 2) Determine which new O-ring fits best in the groove.
 *Proper fit should be snug without extending past the outside or inside diameter of the groove. O-ring should not bind or pinch. (Does not apply to kit No. 905573)

***Note:** Early units of the union end ball valve shipped with a different O-ring groove dimension than the current production. Two O-rings are provided with this kit—one for each design. Select the O-ring to meet your application.

- 3) Apply a thin film of food grade petroleum based O-ring lubricant to the new O-ring.
- 4) Place the new ring into the groove of the union connection and screw union connection back together.

**CALIFORNIA PROPOSITION 65 WARNING**

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. (California law requires this warning to be given to customers in the State of California.)

For more information: www.watts.com/prop65

Limited Warranty: FEBCO warrants each product to be free from defects in material and workmanship under normal usage for a period of one year from the date of original shipment. In the event of such defects within the warranty period, the Company will, at its option, replace or recondition the product without charge. This shall constitute the sole and exclusive remedy for breach of warranty, and the Company shall not be responsible for any incidental, special or consequential damages, including without limitation, lost profits or the cost of repairing or replacing other property which is damaged if this product does not work properly, other costs resulting from labor charges, delays, vandalism, negligence, fouling caused by foreign material, damage from adverse water conditions, chemical, or any other circumstances over which the Company has no control. This warranty shall be invalidated by any abuse, misuse, misapplication or improper installation of the product. **THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** Any implied warranties that are imposed by law are limited in duration to one year.

Some States do not allow limitations on how long an implied warranty lasts, and some States do not allow the exclusion or limitation of incidental or consequential damages. Therefore the above limitations may not apply to you. This Limited Warranty gives you specific legal rights, and you may have other rights that vary from State to State. You should consult applicable state laws to determine your rights.



A Division of Watts Water Technologies, Inc.

USA: 4381 N. Brawley • Ste. 102 • Fresno, CA • 93722 • Tel. (559) 441-5300 • Fax: (559) 441-5301 • www.FEBCOonline.com
 Canada: 5435 North Service Rd. • Burlington, ONT. • L7L 5H7 • Tel. (905) 332-4090 • Fax: (905) 332-7068 • www.FEBCOonline.ca

CALIFORNIA PROPOSITION 65 WARNING

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. (California law requires this warning to be given to customers in the State of California.)

For more information: www.watts.com/prop65

Limited Warranty: FEBCO warrants each product to be free from defects in material and workmanship under normal usage for a period of one year from the date of original shipment. In the event of such defects within the warranty period, the Company will, at its option, replace or recondition the product without charge. This shall constitute the sole and exclusive remedy for breach of warranty, and the Company shall not be responsible for any incidental, special or consequential damages, including without limitation, lost profits or the cost of repairing or replacing other property which is damaged if this product does not work properly, other costs resulting from labor charges, delays, vandalism, negligence, fouling caused by foreign material, damage from adverse water conditions, chemical, or any other circumstances over which the Company has no control. This warranty shall be invalidated by any abuse, misuse, misapplication or improper installation of the product. **THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** Any implied warranties that are imposed by law are limited in duration to one year.

Some States do not allow limitations on how long an implied warranty lasts, and some States do not allow the exclusion or limitation of incidental or consequential damages. Therefore the above limitations may not apply to you. This Limited Warranty gives you specific legal rights, and you may have other rights that vary from State to State. You should consult applicable state laws to determine your rights.



A Division of Watts Water Technologies, Inc.

USA: 4381 N. Brawley • Ste. 102 • Fresno, CA • 93722 • Tel. (559) 441-5300 • Fax: (559) 441-5301 • www.FEBCOonline.com
Canada: 5435 North Service Rd. • Burlington, ONT. • L7L 5H7 • Tel. (905) 332-4090 • Fax: (905) 332-7068 • www.FEBCOonline.ca

IS-F-622UF/UFT 0633

EDP# 980141

© FEBCO, 2007

IS-F-622UF/UFT

INSTALLATION INSTRUCTIONS

Series 622UF/UFT

Union Ball Valves

Sizes: 1/2" - 2" (15 – 50mm)

Installation Instructions

Kit Part No: 905573, 905574, 905575, 905576, 905577, & 905578
Instruction #2 does not apply to Kit No. 905573

- 1) Unscrew the union connection and remove old O-ring.
- 2) Determine which new O-ring fits best in the groove.
*Proper fit should be snug without extending past the outside or inside diameter of the groove. O-ring should not bind or pinch. (Does not apply to kit No. 905573)

***Note:** Early units of the union end ball valve shipped with a different O-ring groove dimension than the current production. Two O-rings are provided with this kit—one for each design. Select the O-ring to meet your application.

- 3) Apply a thin film of food grade petroleum based O-ring lubricant to the new O-ring.
- 4) Place the new ring into the groove of the union connection and screw union connection back together.

