



Residential/Construction, Power Outlets & Temporary Power

Product #: U050

Short Description: 50A SURFACE UNMTRD

SPECIFICATIONS

| OI LOII IOATTONO | |
|--------------------------------|--------------------------------------|
| Category | Pow er Outlets & Temporary Pow er |
| Mounting | Surface |
| Heads | 1 |
| Metering | Unmetered |
| Receptacles | 10-50R |
| Feed | Overhead |
| AIC | 10,000 |
| Amps | 50.0 |
| Cabinet Size | 5 X 7 |
| Circuit Protection | No |
| Hub Provision | Yes |
| Installed Breaker | None |
| Load Center | None |
| Loop Feed | No |
| Phase | 1 |
| Suitable for Service Equipment | No |
| Standard Package | 4 |
| Stock Class Code | Stock |
| Certification | Non-UL |
| Unit Weight | 4.5 |
| UPC | 078456756930 |
| Volts | 120/240 |
| | |

Photo Not Available

Photo Not Available

Midw est Electric's Temporary Pow er and Pow er Outlets are a means of providing pow er required by various construction trades, residential sites, and mobile electrical applications. Temporary Pow er and Pow er Outlets offer one or more receptacles, with or without overcurrent protection, disconnecting, metering, and/or pedestal mounting functions, in a single enclosure of G-90 zinc-coated steel. The NEMA 3R rainproof enclosure is lockable and engineered to provide maximum protection against w eather, vandalism, and normal field use.

Copyright Midw est Electric Products, Inc. 2006