

Application Information

Where electrical power enters a building or other structure, the National Electrical Code (NEC) requires electrical distribution equipment rated as “Service Entrance.” Such service equipment usually consists of one main breaker disconnect or space for up to 6 main disconnects (Ref. 2008 NEC Article 230.71). Midwest Models meet these NEC requirements and are UL listed as service entrance equipment.

Service entrance products are typically utilized on single family residences and mobile homes. Additionally, service entrance for mobile homes is generally located within 30 feet of the mobile home (Ref. 2008 NEC Article 550.32). This location requirement by the NEC and the common use of underground service feeders, combine to make service entrance on a pedestal the preferred installation method by many park owners. Midwest offers a broad range of pedestal units, factory assembled and wired, with loop feed lugs to reduce installation time and labor expense. Midwest also offers a wide selection of surface units for single family residences and mobile home sites.



R281CB1



CLOSED

OPEN

R282EB1A

Specifications and Features

- Heavy galvanized “G90” 16-gauge steel, with highest quality electro-deposition finish, resists corrosion and fading
- 200 or 125 amp continuous duty meter socket with meter guides and reinforced jaws for ring and ringless type sockets
- Utility meter socket compartment barriered from breaker mains for utility power protection
- UL listed “Suitable for use as service equipment”
- Rated NEMA 3R - weather proof equipment
- All terminals accept copper or aluminum wire for added installation flexibility
- Doors have padlock provision to prevent unauthorized entry
- Supplied with 12-2 Cu/Al equipment ground lug
- 120/240 Volt
- Note: Ringless metered units come standard with horn bypass
- All GFCI Duplexes are listed as Weather Resistant and Tamper Resistant as required by 2008 NEC in Article 406.8 and 406.11.

Post Models:

- 200 Amp Factory wired loop feed lugs
- Removable post door allows lay in wiring
- Rolled edge post bottoms to protect service cable
- Posts available with stud terminations to accept compression type lugs
- Locking hasp for utility seal on post covers

Technical Data

MODEL NUMBER*	HUB OPENING	REPLACEMENT PARTS		CABINET SIZE	ENCLOSURE STYLE page 28	CABINET DIMENSIONS			KNOCKOUT FIGURE page 29	AIC
		METER SOCKET	POST LUGS			HEIGHT	WIDTH	DEPTH		
						A	B	C		
MS251C	Y	MW200M	—	17 X 26	E	26-1/4"	17-1/2"	5-1/2"	10	10,000
MS252C	Y	MW200M	—	17 X 26	E	26-1/4"	17-1/2"	5-1/2"	10	10,000
MS252E014	Y	*	—	14 X 31	E	14-3/4"	31-5/16"	5-7/8"	7B	10,000
MS45500C	N	265A5264P2	—	31 X 33	E	33-1/10"	30-1/2"	6-1/10"	P. 32	22,000
MS45508C	N	265A5264P2	—	31 X 33	E	33-1/10"	30-1/2"	6-1/10"	P. 32	22,000
R100C	Y	MSR100930	—	9 X 30	C	30"	9-3/4"	5-3/16"	3	10,000
R100T	Y	MSR100930	—	9 X 30	C	30"	9-3/4"	5-3/16"	3	10,000
R101C	Y	MSR100930	—	9 X 30	C	30"	9-3/4"	5-3/16"	3	10,000
R101CB2	Y	MW200R	—	14 X 26	D	26-1/4"	14-3/4"	4-9/16"	6	10,000
R101CB2LK	Y	MW200R	—	14 X 26	D	26-1/4"	14-3/4"	4-9/16"	6	10,000
R101CB2010	Y	MW200R	—	14 X 26	D	26-1/4"	14-3/4"	4-9/16"	6	10,000
R101CB6	N	MSR100P9	LT100B250	9PT				See page 30		10,000
R101CB6HP	N	MSR100P9	LT200B350	9HP				See page 30		10,000
R101CP6	N	MSR100P9	LT100S250	9PT				See page 30		10,000
R101CP6HP	N	MSR100P9	LT200S350	9HP				See page 30		10,000
R102CB2	Y	MW200R	—	14 X 26	D	26-1/4"	14-3/4"	4-9/16"	6	10,000
R102CB2LK	Y	MW200R	—	14 X 26	D	26-1/4"	14-3/4"	4-9/16"	6	10,000
R102E	Y	MSR100930	—	9 X 30	C	29-1/2"	9-1/4"	5-3/16"	1	10,000
R102EN	Y	MSR100930	—	9 X 30	C	29-1/2"	9-1/4"	5-3/16"	1	10,000
R181CB1	Y	MSRS	—	14 X 28	D	28-1/2"	14-3/10"	4-4/5"	6	10,000
R200T	Y	MW200R	—	14 X 38	C	38-3/8"	14-3/4"	6-3/8"	8	10,000
R208CP6HP	N	MW200R	LT200S350	14HP				See page 30		10,000
R208CR2A	Y (2)	MW200R	—	14 X 28	C	28-5/8"	14-3/4"	6-3/8"	8	10,000
R208CR2A034	Y	265A5264P8	—	14 X 28	C	28-5/8"	14-3/4"	6-3/8"	8	10,000
R211CP6	N	MSRS	—	*				See page 30		10,000
R225CP6	N	MW200R	LT200S350	14PT						10,000
R2502CP6	N	MSRS	—	*	*	*	*	*	*	10,000
R256EB1A	Y	198B8601G70	—	14 X 26	D	26-1/4"	14-3/4"	4-9/16"	6	10,000
R256EB1018A	Y	198B8601G70	—	14 X 26	D	26-1/4"	14-3/4"	4-9/16"	6	10,000
R256EB1NA	Y	198B8601G70	—	14 X 26	D	26-1/4"	14-3/4"	4-9/16"	6	10,000
R280T	Y	MW200R	—	9 X 32	C	32-1/4"	9-3/4"	5-11/16"	4	10,000
R280TP6HP	N	MW200R	LT200S350	9HP				See page 30		10,000
R281C1	Y	MSRS	—	9 X 30	D	30-1/4"	9-5/16"	4-3/4"	12	22,000
R281C1034	Y	265A5264P8	—	14 X 32	D	32-1/2"	14-1/2"	5-7/16"	15	22,000
R281C1B6H	N	MSRP	LT200B350	6H				See page 31		22,000
R281C1B6H034	N	265A5264P8	LT200B350	6H034				See page 31		22,000
R281C1P6H	N	MSRP	LT200S350	6H				See page 31		22,000
R281C1P6H034	N	265A5264P8	LT200S350	6H034				See page 31		22,000
R281C1S6HC	N	MSRP	LT200SS	6H				See page 31		22,000
R281CB1	Y	MSRS	—	14 X 28	D	28-5/8"	14-3/8"	4-3/4"	13	22,000
R281CB1034	Y	265A5264P8	—	14 X 28	D	28-5/8"	14-3/8"	4-3/4"	13	22,000
R281CB1LK	Y	MSRS	—	14 X 28	D	28-5/8"	14-3/8"	4-3/4"	13	22,000
R281E1B6H	N	MSRP	LT200B350	6H				See page 31		22,000
R281E1B6H034	N	265A5264P8	LT200B350	6H034				See page 31		22,000
R281E1P6H	N	MSRP	LT200S350	6H				See page 31		22,000
R281E1P6H034	N	265A5264P8	LT200S350	6H034				See page 31		22,000
R281EB1	Y	MSRS	—	14 X 28	D	28-5/8"	14-3/8"	4-3/4"	13	22,000
R281EB1034	Y	265A5264P8	—	14 X 28	D	28-5/8"	14-3/8"	4-3/4"	13	22,000
R282C1B6H	N	MSRP	LT200B350	6H				See page 31		22,000
R282C1P6H	N	MSRP	LT200S350	6H				See page 31		22,000
R282CB1	Y	MSRS	—	14 X 28	D	28-5/8"	14-3/8"	4-3/4"	13	22,000
R282CB1LK	Y	MSRS	—	14 X 28	D	28-5/8"	14-3/8"	4-3/4"	13	22,000
R282E1B6H	N	MSRP	LT200B350	6H				See page 31		22,000
R282E1P6H	N	MSRP	LT200S350	6H				See page 31		22,000
R282EB1	Y	MSRS	—	14 X 28	D	28-5/8"	14-3/8"	4-3/4"	13	22,000
R460CP6034	N	265A5264P10	*	14PT				See page 30		22,000

* Not all models listed; contact local representative for other models and details.

Data subject to change without notice.