



Catalog No. R055G

Description: 70A SURFACE MTRD 50/20GFCI

UPC No 784567200614

Home > Power Outlets & Temporary Power

Midwest Electric's Temporary Power and Power Outlets are a means of providing power required by various construction trades, residential sites, and mobile electrical applications. Temporary Power and Power Outlets offer one or more receptacles, with or without overcurrent protection, disconnecting, metering, and/or pedestal mounting functions, in a single enclosure of G-90 zinc-coated steel. The NEMA 3R rainproof enclosure is lockable and engineered to provide maximum protection against weather, vandalism, and normal field use.

Descriptors	
Category	Power Outlets & Temporary Power
Specifications	

Specifications	
Mounting	Surface
Heads	1
Metering	Ringless
Receptacles	14-50R, 5-20R2, 50/20
Feed	Overhead
AIC	10,000
Amps	70.0 A
Cabinet Size	9 X 30
Circuit Protection	Yes
Hub Provision	Yes
Installed Breaker	CB250, GFI120
Load Center	LC33N1
Loop Feed	Yes
Phase	1
Suitable for Service Equipment	Yes
Unit Weight	25.0 lb
Volts	120/240

Classifications	
Standard Package	1
Stock Class Code	Non Stock

Approvals	
Certification	UL/CUL

midwestelectric.com Created on: 07/30/2018