



Representative Image

Catalog No. MGU323R

Description: 100A GD DISC 3P NONFUSE TYP3R 240V

UPC No 783164459654

Home > Safety Switches > General Duty

- Designed for residential and light commercial applications where duty is not severe.
- Listed to UL standard 98 enclosed and dead front switches.
- Suitable for use as service equipment when installed in accordance with the National Electrical Code.
- Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches.
- Meets or exceeds NEMA KS1 standard for enclosed switches - type GD.
- Fusible and non-fusible switches available.
- Quick-make, quick-break mechanism (30-200 amp).
- 60/75°C conductor rating.

Descriptors

Category	General Duty
GO Schedule	131AM

Specifications

Voltage	240 Vac
Amperage	100 A
Poles	3
Wires	3
Fusing	Non-Fusible
Enclosure Type	NEMA 3R (Outdoor)
Wire Range	10-1/0
240 Vac, NEC Std, 1-ph	15.0 hp
240 Vac, NEC Std, 3-ph	30.0 hp

Classifications

CSA Certified	CUL
UL Listed	Yes

Dimensions

Height	15.6 in
Depth	5.0 in
Width	9.3 in

Publications

Title	Publication No.	Publication Type
Safety Switch Outline Drawing 200A General Duty Disconnect, NEMA Type 3R Enclosure	1013093SH7	Drawings-Outline and Dimensional
Midwest Safety Switch Quick Selection Guide Midwest Safety Switch Quick Selection Guide	MET-041	Application and Technical
Midwest Safety Switches Line Card	MEA-010	Brochures
residential to commercial. Our General Duty switches are designed for residential and light commercial applications where duty is not severe. The Heavy Duty switches are designed for commercial and industrial applications where safety and superior reliability are essential. Midwest Safety Switches Line Card	-010	Brochures
he Heavy Duty switches are designed for commercial and industrial applications where safety and superior reliability are essential. Midwest Safety Switches	MET-029	Brochures
v. C. 12 pages. Rugged, reliable and easy to install		

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.