



Representative Image

Catalog No. MGU324

Description: 200A GD DISC 3P NONFUSE TYP1 240V

UPC No 783164459661

Home > Safety Switches > General Duty

- Designed for residential and light commercial applications where duty is not severe.
- Listed to UL standard 98 enclosed and dead front switches.
- Suitable for use as service equipment when installed in accordance with the National Electrical Code.
- Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches.
- Meets or exceeds NEMA KS1 standard for enclosed switches - type GD.
- Fusible and non-fusible switches available.
- Quick-make, quick-break mechanism (30-200 amp).
- 60/75°C conductor rating.

Descriptors

Category	General Duty
GO Schedule	131AM

Specifications

Voltage	240 Vac
Amperage	200 A
Poles	3
Wires	3
Fusing	Non-Fusible
Enclosure Type	NEMA 1 (Indoor)
Wire Range	2-250
240 Vac, NEC Std, 3-ph	50.0 hp

Classifications

CSA Certified	CUL
UL Listed	Yes

Dimensions

Height	29.1 in
Depth	5.2 in
Width	13.4 in

Publications

Title	Publication No.	Publication Type
Midwest Safety Switch Quick Selection Guide		
Midwest Safety Switch Quick Selection Guide	MET-041	Application and Technical
Midwest Safety Switches		
Rev. B. 12 pages. Rugged, reliable and easy to install	MET-029	Brochures
Midwest Safety Switches Line Card		
	MEA-010	Brochures
2 pages. Midwest offers a variety of Safety Switches to meet many common applications from residential to commercial. Our General Duty switches are designed for residential and light commercial applications where duty is not severe. The Heavy Duty switches are designed for commercial and industrial applications where safety and superior reliability are essential.		
Safety Switch Outline Drawing		
200A General Duty Disconnect, NEMA Type 1 Enclosure	1013093SH8	Drawings-Outline and Dimensional

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.