



Representative Image

Catalog No. MHF361R

Description: 30A HD DISC 3P FUSIBLE TYP3R 600V

UPC No 783164459852

Home > Safety Switches > Heavy Duty

- Designed for commercial and industrial applications where safety, high performance and continuity of service are essential.
- Listed to UL standard 98 enclosed and dead front switches.
- Suitable for use as service equipment when installed in accordance with the National Electrical Code.
- Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches.
- Meets or exceeds NEMA KS1 standard for enclosed switches - type HD.
- Fusible and non-fusible switches available.
- Quick-make, quick-break mechanism.
- 60/75°C conductor rating.
- Full cover interlocks.

Descriptors

Category	Heavy Duty
GO Schedule	131M

Specifications

Voltage	600 Vac
Amperage	30 A
Poles	3
Wires	3
Fusing	Fusible
Enclosure Type	NEMA 3R (Outdoor)
Wire Range	12-2

Classifications

CSA Certified	CUL
UL Listed	Yes

Dimensions

Height	13.1 in
Depth	4.0 in
Width	8.2 in

Publications

Title	Publication No.	Publication Type
Midwest Safety Switch Quick Selection Guide Midwest Safety Switch Quick Selection Guide	MET-041	Application and Technical
Midwest Safety Switches Rev. B. 12 pages. Rugged, reliable and easy to install	MET-029	Brochures
Safety Switch Outline Drawing 60A, NEMA Type 3R Enclosure	1013093SH1	Drawings-Outline and Dimensional
Midwest Safety Switches Line Card	MEA-010	Brochures

2 pages. Midwest offers a variety of Safety Switches to meet many common applications from residential to commercial. Our General Duty switches are designed for residential and light commercial applications where duty is not severe. The Heavy Duty switches are designed for commercial and industrial applications where safety and superior reliability are essential.

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.