



Catalog No. U036G

Description: 40A SURFACE UNMTRD 20/20

UPC No 784567568509

Home > Power Outlets & Temporary Power

Midwest Electric's Temporary Power and Power Outlets are a means of providing power required by various construction trades, residential sites, and mobile electrical applications. Temporary Power and Power Outlets offer one or more receptacles, with or without overcurrent protection, disconnecting, metering, and/or pedestal mounting functions, in a single enclosure of G-90 zinc-coated steel. The NEMA 3R rainproof enclosure is lockable and engineered to provide maximum protection against weather, vandalism, and normal field use.

Representative Image

Descriptors	
Category	Power Outlets & Temporary Power

Specifications

Mounting	Surface
Heads	1
Metering	Unmetered
Receptacles	6-20R, 5-20R2
Feed	Overhead
AIC	10,000
Amps	40.0 A
Cabinet Size	6 X 14
Circuit Protection	Yes
Hub Provision	Yes
Installed Breaker	CB220, GFI120
Load Center	LC33N7
Loop Feed	No
Phase	1
Suitable for Service Equipment	Yes
Unit Weight	10.0 lb
Volts	120/240

Classifications

Standard Package	4
Stock Class Code	Non Stock

Approvals

Certification	UL/CUL