



Catalog No. MGF321N

Description: 30A GD DISC 3P FUSIBLE TYP1 240V

UPC No 783164459524

Home > Safety Switches > General Duty

- Designed for residential and light commercial applications where duty is not severe. Listed to UL standard 98 enclosed and dead front switches.
- Suitable for use as service equipment when installed in accordance with the National Electrical Code.
- Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches type GD. Fusible and non-fusible switches available. Quick-make, quick-break mechanism (30-200 amp). 60/75°C conductor rating.

Descriptors	
Category	General Duty
GO Schedule	131AM

Specifications				
Voltage	240 Vac			
Amperage	30 A			
Poles	3			
Wires	4			
Fusing	Fusible			
Enclosure Type	NEMA 1 (Indoor)			
Wire Range	14-8 CU;12-8 AL			
240 Vac, NEC Std, 1-ph	1.5 hp			
240 Vac, NEC Std, 3-ph	3.0 hp			
240 Vac, Time Delay, 1-ph	3.0 hp			
240 Vac, Time Delay, 3-ph	7.5 hp			

Classifications	
CSA Certified	CUL
UL Listed	Yes

Dimensions	
Height	10.3 in
Height Depth	3.3 in
Width	6.4 in

midwestelectric.com Created on: 07/23/2018

Publication No.	Publication Type
	Application and
MET-041	Technical
MET-029	Brochures
Drawings-Outline ar Dimensional	
MEA-010	Brochures
	MET-041 MET-029 1013093SH4

2 pages. Midwest offers a variety of Safety Switches to meet many common applications from residential to commercial. Our General Duty switches are designed for residential and light commercial applications where duty is not severe. The Heavy Duty switches are designed for commercial and industrial applications where safety and superior reliability are essential.

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.

midwestelectric.com Created on: 07/23/2018

Dublications