



Representative Image

Catalog No. MHF322N

Description: 60A HD DISC 3P FUSIBLE TYP1 240V

UPC No 783164459784

Home > Safety Switches > Heavy Duty

- · Designed for commercial and industrial applications where safety, high performance and continuity of
- Listed to UL standard 98 enclosed and dead front switches.
- Suitable for use as service equipment when installed in accordance with the National Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches.

 Meets or exceeds NEMA KS1 standard for enclosed switches type HD.

 Fusible and non-fusible switches available.

 Quick-make, quick-break mechanism.

 60/75°C conductor rating.

- Full cover interlocks.

Descriptors	
Category	Heavy Duty
GO Schedule	131M

Specifications		
Voltage	240 Vac	
Amperage	60 A	
Poles	3	
Wires	4	
Fusing	Fusible	
Enclosure Type	NEMA 1 (Indoor)	
Wire Range	12-2	
240 Vac, NEC Std, 1-ph	3.0 hp	
240 Vac, NEC Std, 3-ph	7.5 hp	
240 Vac, Time Delay, 1-ph	10.0 hp	
240 Vac, Time Delay, 3-ph	15.0 hp	

Classifications				
CSA Certified	CUL			
UL Listed	Yes			

Dimensions	
Height	17.6 in
Height Depth	5.0 in
Width	9.4 in

midwestelectric.com Created on: 07/23/2018

Publication No.	Publication Type
	Application and Technical
MET-041	
MET-029	Brochures
	Drawings-Outline and Dimensional
1013093SH2	
MEA-010	Brochures
	MET-041 MET-029 1013093SH2

2 pages. Midwest offers a variety of Safety Switches to meet many common applications from residential to commercial. Our General Duty switches are designed for residential and light commercial applications where duty is not severe. The Heavy Duty switches are designed for commercial and industrial applications where safety and superior reliability are essential.

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.

midwestelectric.com Created on: 07/23/2018

Dublications