



Representative Image

Catalog No. U058CB6

Description: 80A B/B POST UNMTRD 50/30

UPC No 784567202304

Home > Power Outlets & Temporary Power

Midwest Electric's Temporary Power and Power Outlets are a means of providing power required by various construction trades, residential sites, and mobile electrical applications. Temporary Power and Power Outlets offer one or more receptacles, with or without overcurrent protection, disconnecting, metering, and/or pedestal mounting functions, in a single enclosure of G-90 zinc-coated steel. The NEMA 3R rainproof enclosure is lockable and engineered to provide maximum protection against weather, vandalism, and normal field use.

Descriptors

Category	Power Outlets & Temporary Power
----------	---------------------------------

Specifications

Mounting	Pedestal - Earth Burial
Heads	2
Metering	Unmetered
Receptacles	14-50R, R32U
Feed	Underground
AIC	10,000
Amps	80.0 A
Circuit Protection	Yes
Hub Provision	No
Installed Breaker	CB130, CB250
Load Center	LC33N1
Loop Feed	Yes
Phase	1
Suitable for Service Equipment	Yes
Unit Weight	62.0 lb
Volts	120/240

Classifications

Standard Package	1
Stock Class Code	Non Stock

Approvals

Certification	UL/CUL
---------------	--------