

# SAFETY DATA SHEET NO. 514-A HOT DIE

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

#### 1. Identification

**Product identifier** 

Product name NO. 514-A HOT DIE

**Product number** F0053-035, F0053-039, F0053-040

Recommended use of the chemical and restrictions on use

**Uses advised against**No specific uses advised against are identified.

Details of the supplier of the safety data sheet

Manufacturer Lubriplate Lubricants Co.

Corporate Headquarters 129 Lockwood Street Newark, NJ 07105

Midwest Office & Plant 1500 Oakdale Ave. Toledo, OH 43605 419-691-2491 419-693-3806

Emergency telephone number

Emergency telephone Chem-Tel: 1-800-255-3924 (US & Canada only)

01-813-248-0585 (Outside US & Canada) Europe: +49 4262 79 9603

## 2. Hazard(s) identification

## Classification of the substance or mixture

Physical hazards Not Classified

**Health hazards** Skin Irrit. 2 - H315 STOT RE 1 - H372

Environmental hazards Not Classified

Label elements

**Pictogram** 





Signal word Danger

Hazard statements H315 Causes skin irritation.

H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary statements P260 Do not breathe dust.

P264 Wash contaminated skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 If on skin: Wash with plenty of water.
P314 Get medical advice/ attention if you feel unwell.
P321 Specific treatment (see medical advice on this label).
P332+P313 If skin irritation occurs: Get medical advice/ attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P501 Dispose of contents/ container in accordance with national regulations.

Contains Crystalline silica

#### Other hazards

This product does not contain any substances classified as PBT or vPvB.

#### 3. Composition/information on ingredients

#### **Mixtures**

## Residual oils (petroleum,) solvent-refined

10-30%

CAS number: 64742-01-4

#### Classification

Skin Irrit. 2 - H315

Carbon graphite 10-30%

CAS number: 7782-42-5

# Classification

Not Classified

## Distillates (petroleum), hydrotreated heavy naphthenic

10-30%

CAS number: 64742-52-5

#### Classification

Not Classified

# Talc (Mg3H2(SiO3)4) 1-5%

CAS number: 14807-96-6

# Classification

Not Classified

# Magnesium carbonate 1-5%

CAS number: 546-93-0

## Classification

Not Classified

## NO. 514-A HOT DIE

Aluminum stearate 1-5%

CAS number: 300-92-5

Classification Skin Irrit. 2 - H315 Eye Irrit. 2A - H319

Crystalline silica 1-5%

CAS number: 14808-60-7

Classification
Carc. 1B - H350
STOT RE 1 - H372

The full text for all hazard statements is displayed in Section 16.

#### 4. First-aid measures

#### Description of first aid measures

General information Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.

Inhalation Remove affected person from source of contamination. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. Maintain an open airway.

Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on

their side in the recovery position and ensure breathing can take place.

**Ingestion** Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water

or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing

such as collar, tie or belt.

**Skin Contact** Rinse with water.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 10 minutes.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue. Wash

contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth

resuscitation.

# Most important symptoms and effects, both acute and delayed

General information See Section 11 for additional information on health hazards. The severity of the symptoms

described will vary dependent on the concentration and the length of exposure.

**Inhalation** No specific symptoms known.

**Ingestion** May cause irritation.

**Skin contact** Redness. Irritating to skin.

**Eye contact** No specific symptoms known. May be slightly irritating to eyes.

#### Indication of immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

#### 5. Fire-fighting measures

#### Extinguishing media

Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry

powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

#### Special hazards arising from the substance or mixture

•

Specific hazards

None known.

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances:

Harmful gases or vapors.

## Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

## 6. Accidental release measures

# Personal precautions, protective equipment and emergency procedures

Personal precautions

No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material.

**Environmental precautions** 

**Environmental precautions** 

Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

## Methods and material for containment and cleaning up

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Approach the spillage from upwind. Collect spillage with a shovel and broom, or similar and reuse, if possible. Collect and place in suitable waste disposal containers and seal securely. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

## 7. Handling and storage

#### Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Wear protective clothing as described in

Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Keep container tightly sealed when not in use. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

#### Conditions for safe storage, including any incompatibilities

Storage precautions Store away from incompatible materials (see Section 10). Store in accordance with local

regulations. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Utilize retaining walls to prevent soil and water pollution in the event of spillage. The storage area floor should

be leak-tight, jointless and not absorbent.

Storage class Chemical storage.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

#### 8. Exposure controls/Personal protection

#### Control parameters

#### Occupational exposure limits

#### Carbon graphite

Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m³ respirable fraction Long-term exposure limit (8-hour TWA): OSHA 15 particles/cc respirable dust

## Distillates (petroleum), hydrotreated heavy naphthenic

Mineral oil, excluding metal working fluids (pure, highly and severely refined) ACGIH

## Talc (Mg3H2(SiO3)4)

Long-term exposure limit (8-hour TWA): OSHA 20 particles/cc respirable dust Long-term exposure limit (8-hour TWA): ACGIH 0.1 f/cc containing asbestos fibers A1

Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m³ respirable fraction A4

#### Magnesium carbonate

Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³ respirable fraction Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust

#### Crystalline silica

Long-term exposure limit (8-hour TWA): OSHA 0.05 mg/m³ respirable dust Long-term exposure limit (8-hour TWA): ACGIH 0.025 mg/m³ respirable fraction A2

ACGIH = American Conference of Governmental Industrial Hygienists.

OSHA = Occupational Safety and Health Administration.

A1 = Confirmed Human Carcinogen.

A2 = Suspected Human Carcinogen.

A4 = Not Classifiable as a Human Carcinogen.

Carbon graphite (CAS: 7782-42-5)

Immediate danger to life and health

1250 mg/m<sup>3</sup>

Talc (Mg3H2(SiO3)4) (CAS: 14807-96-6)

Immediate danger to life and health

3000 mg/m<sup>3</sup> 3000 mg/m<sup>3</sup>

Crystalline silica (CAS: 14808-60-7)

Immediate danger to life and health

25 mg/m<sup>3</sup> 50 mg/m<sup>3</sup>

#### **Exposure controls**

## Protective equipment







Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimize worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimize exposure.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with OSHA 1910.133. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

Other skin and body protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

Hygiene measures

Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.

## NO. 514-A HOT DIE

Respiratory protection Respiratory protection complying with an approved standard should be worn if a risk

assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with OSHA 1910.134. Full face mask respirators with replaceable filter cartridges should comply with OSHA 1910.134. Half mask and quarter mask respirators with replaceable

filter cartridges should comply with OSHA 1910.134.

Environmental exposure

controls

Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## 9. Physical and chemical properties

## Information on basic physical and chemical properties

Appearance Solid. [grease]

Color Black.

Odor Mineral oil

Odor threshold Not available.

**pH** Not available.

Melting point Not available.

Initial boiling point and range >288°C (>550.4°F)

Flash point 266°C/510.8°F Cleveland open cup.

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or

explosive limits

Lower flammable/explosive limit: 0.9 % Upper flammable/explosive limit: 7 %

Vapor pressure <0.0013 kPa @ 20°C

Vapor density > 5

Relative density 1.14

Solubility(ies) Insoluble in water.

Partition coefficient Not available.

**Auto-ignition temperature** Not available.

**Decomposition Temperature** Not available.

Viscosity Not available.

**Explosive properties** Not considered to be explosive.

Oxidizing properties Does not meet the criteria for classification as oxidizing.

# 10. Stability and reactivity

**Reactivity** See the other subsections of this section for further details.

Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

## NO. 514-A HOT DIE

Possibility of hazardous

reactions

No potentially hazardous reactions known.

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

Materials to avoid No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

## 11. Toxicological information

#### Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅o) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD<sub>50</sub>) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC50) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Irritating.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitization

**Respiratory sensitization** Based on available data the classification criteria are not met.

Skin sensitization

**Skin sensitization** Based on available data the classification criteria are not met.

Germ cell mutagenicity

**Genotoxicity - in vitro**Based on available data the classification criteria are not met.

Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

IARC carcinogenicity Contains a substance/a group of substances which may cause cancer. IARC Group 1

Carcinogenic to humans.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -

development

Based on available data the classification criteria are not met.

# Specific target organ toxicity - single exposure

**STOT - single exposure**Not classified as a specific target organ toxicant after a single exposure.

## Specific target organ toxicity - repeated exposure

STOT - repeated exposure STOT RE 2 - H373 May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Aspiration hazard Not relevant. Solid.

#### NO. 514-A HOT DIE

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

**Inhalation** No specific symptoms known.

**Ingestion** May cause irritation.

**Skin Contact** Redness. Irritating to skin.

Eye contact No specific symptoms known.

Route of exposure Ingestion Inhalation Skin and/or eye contact

**Target Organs** No specific target organs known.

Toxicological information on ingredients.

Crystalline silica

Acute toxicity - oral

Notes (oral LD<sub>50</sub>) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD<sub>50</sub>) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC<sub>50</sub>) Based on available data the classification criteria are not met.

Skin corrosion/irritation

**Animal data**Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye Based on available data the classification criteria are not met.

damage/irritation

Respiratory sensitization

Respiratory sensitization Based on available data the classification criteria are not met.

Skin sensitization

**Skin sensitization** Based on available data the classification criteria are not met.

Germ cell mutagenicity

**Genotoxicity - in vitro**Based on available data the classification criteria are not met.

Carcinogenicity

**Carcinogenicity** May cause cancer.

IARC carcinogenicity IARC Group 1 Carcinogenic to humans.

NTP carcinogenicity Known human carcinogen.

Reproductive toxicity

**Reproductive toxicity -** Based on available data the classification criteria are not met.

fertility

**Reproductive toxicity -** Based on available data the classification criteria are not met.

development

Specific target organ toxicity - single exposure

#### NO. 514-A HOT DIE

**STOT - single exposure** Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure STOT RE 1 - H372

Aspiration hazard

**Aspiration hazard** Not relevant. Solid.

General information

May cause cancer after repeated exposure. Risk of cancer depends on duration

and level of exposure. The severity of the symptoms described will vary dependent

on the concentration and the length of exposure.

**Inhalation** No specific symptoms known.

**Ingestion** No specific symptoms known.

**Skin Contact** Prolonged contact may cause dryness of the skin.

**Eye contact** No specific symptoms known.

Route of exposure Ingestion Inhalation Skin and/or eye contact

**Target Organs** No specific target organs known.

## 12. Ecological information

**Ecotoxicity** Not regarded as dangerous for the environment. However, large or frequent spills may have

hazardous effects on the environment.

**Toxicity** Based on available data the classification criteria are not met.

Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient Not available.

Mobility in soil

Mobility No data available.

Other adverse effects

Other adverse effects None known.

## 13. Disposal considerations

## Waste treatment methods

General information

The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

**Disposal methods**Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a

licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Waste packaging should be collected for reuse or recycling. Incineration or landfill should only be considered when recycling is not feasible.

## 14. Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, DOT).

**UN Number** 

UN No. (International) Not applicable.

UN No. (DOT) Not applicable.

UN proper shipping name

Proper shipping name

(International)

Not applicable.

Proper shipping name (DOT) Not applicable.

Transport hazard class(es)

Transport Labels

No transport warning sign required.

(International)

**DOT transport labels** 

No transport warning sign required.

Packing group

Packing group (International) Not applicable.

DOT packing group Not applicable.

**Environmental hazards** 

**Environmentally Hazardous Substance** 

No.

Special precautions for user

Not applicable.

DOT reportable quantity Not applicable.

DOT TIH Zone Not applicable.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

# 15. Regulatory information

## **US Federal Regulations**

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed or exempt.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

None of the ingredients are listed or exempt.

## SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed or exempt.

## SARA 313 Emission Reporting

The following ingredients are listed or exempt:

Residues (petroleum), atm. tower

0 %

#### **CAA Accidental Release Prevention**

None of the ingredients are listed or exempt.

## FDA - Essential Chemical

None of the ingredients are listed or exempt.

#### FDA - Precursor Chemical

None of the ingredients are listed or exempt.

## SARA (311/312) Hazard Categories

None of the ingredients are listed or exempt.

## **OSHA Highly Hazardous Chemicals**

None of the ingredients are listed or exempt.

# **US State Regulations**

## California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are listed or exempt.

## California Air Toxics "Hot Spots" (A-I)

None of the ingredients are listed or exempt.

## California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed or exempt.

## California Directors List of Hazardous Substances

The following ingredients are listed or exempt:

Carbon graphite

Talc (Mg3H2(SiO3)4)

## Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

Carbon graphite

Crystalline silica

Talc (Mg3H2(SiO3)4)

Magnesium carbonate

## Rhode Island "Right To Know" List

The following ingredients are listed or exempt:

Carbon graphite

Crystalline silica

Talc (Mg3H2(SiO3)4)

Magnesium carbonate

#### NO. 514-A HOT DIE

## Minnesota "Right To Know" List

The following ingredients are listed or exempt:

Carbon graphite

Crystalline silica

Talc (Mg3H2(SiO3)4)

Magnesium carbonate

## New Jersey "Right To Know" List

The following ingredients are listed or exempt:

Carbon graphite

Crystalline silica

Talc (Mg3H2(SiO3)4)

Magnesium carbonate

## Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

Carbon graphite

Crystalline silica

Talc (Mg3H2(SiO3)4)

#### **Inventories**

## US - TSCA

The following ingredients are listed or exempt:

Residual oils (petroleum,) solvent-refined

Petroleum Resins

Residues (petroleum), atm. tower

Distillates (petroleum), hydrotreated heavy naphthenic

Carbon graphite

Crystalline silica

Aluminum stearate

Talc (Mg3H2(SiO3)4)

Magnesium carbonate

Dolomite

## US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

## 16. Other information

Classification abbreviations Skin Irrit. = Skin irritation

and acronyms STOT RE = Specific target organ toxicity-repeated exposure

Training advice Read and follow manufacturer's recommendations. Only trained personnel should use this

material.

Revision date 8/28/2018

**SDS No.** 5171

# NO. 514-A HOT DIE

Hazard statements in full H315 Causes skin irritation.

H319 Causes serious eye irritation.

H350 May cause cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

**End of SDS** 

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.