



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE MO-LITH No. 2

DESCRIPTION

LUBRIPLATE Mo-Lith No. 2 is exactly what the name indicates -- a moly-lithium lubricant -- containing Technical Fine Molybdenum Disulfide. The use of moly has been widely acclaimed by various members in the lubricant field: however, unless the correct amount is used, it has little affect on the end result. Likewise, the base grease that carries the moly must be of premium quality or the benefits are not forthcoming. In LUBRIPLATE Mo-Lith No. 2, we have compounded the optimum percentage of moly for the greatest performance.

APPLICATIONS

Recommended as a primary friction barrier lubricant

ADVANTAGES

- ⇒ Anti-wear/extreme pressure reinforced by the addition of Molybdenum Disulfide (MoS₂)
- ⇒ Non-corrosive
- ⇒ High water resistance

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Type of Thickener		Lithium
Worked Penetration @ 77°F	ASTM D-217	265 to 295
NLGI No.		2
ASTM Dropping Point	ASTM D566	350°F/177°C
Mineral Oil Viscosity SUS @ 100°F	ASTM D-2161	600
cSt @ 40°C	ASTM D-445	112
Color	Visual	Steel Gray

⇒ Contains Molybdenum Disulfide

PACKAGING AVAILABLE

Part No.

Carton, 12/16 oz. Plastic Tubs	L0180-004
Carton, 4/6 lb. Plastic Tubs	L0180-005
35 lb. Pail	L0180-035
120 lb. Quarter Size Drum	L0180-039
430 lb. Full Size Drum	L0180-040
Carton, 40/14½ oz. Cartridges	L0180-098

