



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**  
Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**  
Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**  
Phone: 1-800-733-4755

**PRODUCT DATA**

**LUBRIPLATE STO-FG**

"This product is certified OU Kosher Pareve"  
"This product is Halal certified"

\*NSF International H-1 Registered  
NSF ISO21469 Certification

**DESCRIPTION**

LUBRIPLATE STO-FG is a special, compounded oil recommended for the lubrication of stirrups on bottle filling machines.

**APPLICATIONS**

⇒ Stirrups – Bottle Fillers

**ADVANTAGES**

LUBRIPLATE STO-FG has excellent emulsifying properties to provide a lubricating film on the metal surfaces even in the presence of excessive moisture. LUBRIPLATE STO-FG is also compounded with dispersant type additives to keep the metal surfaces from building up with undesirable residues. This anti-wear oil is designed for areas of "incidental contact" requiring an NSF International H-1 registered product.

**STORAGE RECOMMENDATIONS**

1. Products should be stored between 40°F-120°F.
2. Products should be stored in a dry covered environment.
3. Products should not be stored in warm, direct sunlight.
4. improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.

**Typical Test Data**

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity SUS @ 100°F	ASTM D-2161	350
Viscosity cSt @ 40°C	ASTM D-445	67
ISO		68
SAE Viscosity		20
API Gravity	ASTM D-287	29.0
Color	ASTM D-1500	0.0
Flash Point °F/°C	ASTM D-92	425°F/219°C
Fire Point °F/°C	ASTM D-92	485°F/252°C
Pour Point °F/°C	ASTM D-97	-15°F/-26°C
Four Ball Wear Test	ASTM D-2266	.36 mm

**PACKAGING AVAILABLE**

**Part No.**

5 Gallon Pail L0863-060  
55 Gallon Drum L0863-062

\*NSF International H-1 Registration No. **126120**  
(Meets former USDA 1998 Guidelines)

\*Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

"LUBRIPLATE STO-FG contains no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011."

