



SAFETY DATA SHEET

Gear Shield Extra Heavy - Aerosol

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification

Product identifier

Product name Gear Shield Extra Heavy - Aerosol

Product number L0152-063

Recommended use of the chemical and restrictions on use

Application Petroleum lubricating grease

Uses advised against No specific uses advised against are identified.

Details of the supplier of the safety data sheet

Manufacturer Lubriplate Lubricants Co.
Corporate Headquarters
129 Lockwood Street
Newark, NJ 07105

Midwest Office & Plant
1500 Oakdale Ave.
Toledo, OH 43605
800-733-4755
800-347-5329

Emergency telephone number

Emergency telephone Chem-Tel: 1-800-255-3924 (US & Canada only)
01-813-248-0585 (Outside US & Canada)

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Flam. Aerosol 1 - H222 Press. Gas, Compressed - H280

Health hazards Asp. Tox. 1 - H304

Environmental hazards Aquatic Acute 3 - H402 Aquatic Chronic 3 - H412

Label elements

Pictogram



Signal word

Danger

Hazard statements

H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H412 Harmful to aquatic life with long lasting effects.

Gear Shield Extra Heavy - Aerosol

Precautionary statements	P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.
	P211 Do not spray on an open flame or other ignition source.
	P251 Pressurized container: Do not pierce or burn, even after use
	P273 Avoid release to the environment.
	P301+P310 If swallowed: Immediately call a poison center/ doctor.
	P331 Do NOT induce vomiting.
	P405 Store locked up.
	P410+P403 Protect from sunlight. Store in a well-ventilated place.
	P412 Do not expose to temperatures exceeding 50°C/122°F.
	P501 Dispose of contents/ container in accordance with national regulations.

Contains Distillates (petroleum), hydrotreated light

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

Distillates (petroleum), hydrotreated light		30-60%
CAS number: 64742-47-8		
Classification		
Asp. Tox. 1 - H304		
Petroleum gases, liquefied, sweetened		10-30%
CAS number: 68476-86-8		
Classification		
Flam. Gas 1 - H220		
Distillates (petroleum), hydrotreated heavy naphthenic		5-10%
CAS number: 64742-52-5		
Classification		
Not Classified		
Residual oils (petroleum,) solvent-refined		1-5%
CAS number: 64742-01-4		
Classification		
Skin Irrit. 2 - H315		
zinc oxide		1-5%
CAS number: 1314-13-2		
M factor (Acute) = 1 M factor (Chronic) = 1		
Classification		
Aquatic Acute 1 - H400		
Aquatic Chronic 1 - H410		

Gear Shield Extra Heavy - Aerosol

Carbon black CAS number: 1333-86-4	1-5%
Classification Not Classified	

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures

Description of first aid measures

General information	If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist.
Ingestion	Rinse mouth thoroughly with water. Get medical advice/attention if you feel unwell. Do not induce vomiting unless under the direction of medical personnel.
Skin Contact	Rinse with water.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse with water. Get medical attention if any discomfort continues.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Spray/mists may cause respiratory tract irritation.
Ingestion	Due to the physical nature of this product, it is unlikely that ingestion will occur.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	May be slightly irritating to eyes. May cause discomfort.

Indication of immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. Vapors may form explosive mixtures with air.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

Advice for firefighters

Gear Shield Extra Heavy - Aerosol

Protective actions during firefighting	Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Do not touch or walk into spilled material. Evacuate area. Risk of explosion. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated.
-----------------------------	--

Environmental precautions

Environmental precautions	Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment.
----------------------------------	---

Methods and material for containment and cleaning up

Methods for cleaning up	Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. For waste disposal, see Section 13.
--------------------------------	--

Reference to other sections	For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.
------------------------------------	---

7. Handling and storage

Precautions for safe handling

Usage precautions	Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Avoid exposing aerosol containers to high temperatures or direct sunlight. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid discharge to the aquatic environment. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Avoid contact with eyes. Avoid inhalation of vapors and spray/mists.
--------------------------	---

Advice on general occupational hygiene	Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse.
---	--

Conditions for safe storage, including any incompatibilities

Gear Shield Extra Heavy - Aerosol

Storage precautions Store away from incompatible materials (see Section 10). Keep away from oxidizing materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Protect from sunlight. Do not store near heat sources or expose to high temperatures. Do not expose to temperatures exceeding 50°C/122°F.

Storage class Miscellaneous hazardous material storage.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

Distillates (petroleum), hydrotreated heavy naphthenic

Mineral oil, excluding metal working fluids (pure, highly and severely refined)

ACGIH

zinc oxide

Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³ fume

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust

Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m³ respirable fraction

Short-term exposure limit (15-minute): ACGIH 10 mg/m³ respirable fraction

Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³ respirable fraction

Carbon black

Long-term exposure limit (8-hour TWA): ACGIH 3 mg/m³ inhalable fraction

A3

Long-term exposure limit (8-hour TWA): OSHA 3.5 mg/m³

OSHA = Occupational Safety and Health Administration.

ACGIH = American Conference of Governmental Industrial Hygienists.

A3 = Confirmed Animal Carcinogen with Unknown Relevance to Humans.

zinc oxide (CAS: 1314-13-2)

Immediate danger to life and health 500 mg/m³

Carbon black (CAS: 1333-86-4)

Immediate danger to life and health 1750 mg/m³

Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

No specific hand protection recommended. Avoid contact with skin.

Other skin and body protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Gear Shield Extra Heavy - Aerosol

Hygiene measures	Wash after use and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product.
Respiratory protection	Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with OSHA 1910.134. Full face mask respirators with replaceable filter cartridges should comply with OSHA 1910.134. Half mask and quarter mask respirators with replaceable filter cartridges should comply with OSHA 1910.134.
Environmental exposure controls	Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Aerosol.
Color	Black. Grey.
Odor	Solvent.
Odor threshold	Not available.
pH	Not available.
Melting point	Not available.
Initial boiling point and range	Not available.
Flash point	-18°C/-0.4°F Cleveland open cup.
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 0.9 % Upper flammable/explosive limit: 7 %
Vapor pressure	115 psig @ 54°C
Vapor density	> 1
Relative density	0.98
Solubility(ies)	Insoluble in water.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	31 cSt @ 100°C/212°F
Explosive properties	Not considered to be explosive.
Oxidizing properties	Does not meet the criteria for classification as oxidizing.

10. Stability and reactivity

Reactivity	See the other subsections of this section for further details.
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.

Gear Shield Extra Heavy - Aerosol

Possibility of hazardous reactions	No potentially hazardous reactions known.
Conditions to avoid	Avoid heat, flames and other sources of ignition.
Materials to avoid	Oxidizing materials. Chlorine.
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitization

Respiratory sensitization Based on available data the classification criteria are not met.

Skin sensitization

Skin sensitization Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity

Contains a substance which has been shown to cause cancer in laboratory animals. IARC Group 2A Probably carcinogenic to humans.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard May be fatal if swallowed and enters airways.

General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Gear Shield Extra Heavy - Aerosol

Inhalation	Spray/mists may cause respiratory tract irritation.
Ingestion	Due to the physical nature of this product, it is unlikely that ingestion will occur.
Skin Contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	May be slightly irritating to eyes. May cause discomfort.
Route of exposure	Ingestion Inhalation Skin and/or eye contact
Target Organs	No specific target organs known.

12. Ecological Information

Toxicity	Aquatic Acute 3 - H402 Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting effects.
----------	--

Persistence and degradability

Persistence and degradability	The degradability of the product is not known.
-------------------------------	--

Bioaccumulative potential

Bio-Accumulative Potential	No data available on bioaccumulation.
----------------------------	---------------------------------------

Partition coefficient	Not available.
-----------------------	----------------

Mobility in soil

Mobility	The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.
----------	---

Other adverse effects

Other adverse effects	None known.
-----------------------	-------------

13. Disposal considerations

Waste treatment methods

General information	The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.
---------------------	--

Disposal methods	Do not empty into drains. Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents.
------------------	---

14. Transport information

UN Number

UN No. (TDG)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (DOT)	UN1950

UN proper shipping name

Proper shipping name (TDG)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS

Gear Shield Extra Heavy - Aerosol

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (DOT) AEROSOLS

Transport hazard class(es)

DOT hazard class 2.1

DOT hazard label 2.1

TDG class 2.1

TDG label(s) 2.1

IMDG Class 2.1

ICAO class/division 2.1

Transport labels



DOT transport labels



Environmental hazards

Environmentally Hazardous Substance

No.

Special precautions for user

EmS F-D, S-U

15. Regulatory information

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed or exempt.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

None of the ingredients are listed or exempt.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed or exempt.

SARA 313 Emission Reporting

The following ingredients are listed or exempt:

Residues (petroleum), atm. tower

0 %

zinc oxide

1.0 %

CAA Accidental Release Prevention

None of the ingredients are listed or exempt.

FDA - Essential Chemical

None of the ingredients are listed or exempt.

Gear Shield Extra Heavy - Aerosol

FDA - Precursor Chemical

None of the ingredients are listed or exempt.

SARA (311/312) Hazard Categories

None of the ingredients are listed or exempt.

OSHA Highly Hazardous Chemicals

None of the ingredients are listed or exempt.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

The following ingredients are listed or exempt:

Carbon black

Known to the State of California to cause cancer.

California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed or exempt:

zinc oxide

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed or exempt.

California Directors List of Hazardous Substances

The following ingredients are listed or exempt:

zinc oxide

Carbon black

Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

zinc oxide

Carbon black

Rhode Island "Right To Know" List

The following ingredients are listed or exempt:

zinc oxide

Carbon black

Minnesota "Right To Know" List

The following ingredients are listed or exempt:

zinc oxide

Carbon black

Lithium hydroxide monohydrate

New Jersey "Right To Know" List

The following ingredients are listed or exempt:

Asphalt, oxidized

zinc oxide

Carbon black

Lithium hydroxide monohydrate

Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

zinc oxide

Gear Shield Extra Heavy - Aerosol

Carbon black

Inventories

US - TSCA

The following ingredients are listed or exempt:

Distillates (petroleum), hydrotreated light

Petroleum gases, liquefied, sweetened

Asphalt, oxidized

Residual oils (petroleum), solvent-dewaxed

Residual oils (petroleum,) solvent-refined

Petroleum Resins

Residues (petroleum), atm. tower

Distillates (petroleum), hydrotreated heavy naphthenic

zinc oxide

12-hydroxystearic acid

Carbon black

Tallow

Petroleum oil

Polyisobutylene

US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

16. Other information

Classification abbreviations and acronyms

Aerosol = Aerosol

Press. Gas, Compressed = Gas under pressure: Compressed gas

Aquatic Chronic = Hazardous to the aquatic environment (chronic)

Training advice

Only trained personnel should use this material.

SDS No.

5012

Hazard statements in full

H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H400 Very toxic to aquatic life.

H402 Harmful to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

End of SDS

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.