DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer Product line : W22 Cooling Tower High Efficiency Product code: Three-Phase Catalog #: 03089EP3PCT324V-W22 Frame : 324T Cooling method : IC411 - TEFC Insulation class Mounting : F-2 Duty cycle : Cont.(S1) Rotation¹ : Both (CW and CCW) Ambient temperature : -20°C to +40°C Starting method : Direct On Line Altitude : 1000 m.a.s.l. Approx. weight³ : 2.2 lb : IP55 : 7.85 sq.ft.lb Protection degree Moment of inertia (J) Output [HP] 30 7.5 Poles 4 8 Frequency [Hz] 60 60 Rated voltage [V] 200 200 Rated current [A] 85.5 32.6 L. R. Amperes [A] 693 117 LRC [A] 8.1x(Code J) 3.6x(Code F) No load current [A] 39.1 20.2 Rated speed [RPM] 1780 885 Slip [%] 1.11 1.67 Rated torque [ft.lb] 87.3 43.9 Locked rotor torque [%] 270 160 Breakdown torque [%] 280 170 Service factor 1.25 1.25 Temperature rise 80 K 80 K Locked rotor time 19s (cold) 11s (hot) 90s (cold) 50s (hot) Noise level² 69.0 dB(A) 56.0 dB(A) 25% 89.4 81.0 50% 90.2 82.5 Efficiency (%) 75% 91.0 84.0 100% 91.7 85.5 25% 0.39 0.22 50% 0.64 0.38 Power Factor 75% 0.75 0.50 100% 0.81 0.57 Non drive end Foundation loads Drive end Bearing type 6312 6212 Max. traction : 285 lb 2RS C3 2RS C3 Sealing V'Ring V'Ring Max. compression : 287 lb Lubrication interval Lubricant amount Lubricant type Mobil Polyrex EM Notes

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

, , , , , , , , , , , , , , , , , , , ,					
Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	18/01/2018	1		1/2	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Three Phase induction violor - Squirer Cage								
Customer	:							
		Space heater informa	ntion					
Voltage: 110-127	7/200-240 V							
			T 5					
Rev.		Changes Summary	Performed	Checked	Date			
Performed by								
Checked by				Page	Revision			
Date	18/01/2018			2/2				