## DATA SHEET

## Three Phase Induction Motor - Squirrel Cage

:



## Customer

Product line		: W22 Cooling Tower High Efficiency Product code : Three-Phase		Product code :	12175019			
		Three Thuse		Catalog # :	05089EP3P	CT364V-W22		
Frame		: 364/5T	Cooling	g method	: IC411 - TE	FC		
Insulation class		: F Mountin			: F-2			
Duty cycle		: Cont.(S1) Rotation			: Both (CW and CCW)			
Ambient temperature		: -20°C to +40°C Starting n		g method	hod : Direct On Line			
Altitude		: 1000 m.a.s.l. Approx. w		. weight <sup>3</sup>	: 2.2 lb			
Protection degree		: IP55 Moment of ine		nt of inertia (J)	rtia (J) : 19.9 sq.ft.lb			
Output [HP]		50			12.5			
Poles		4			8			
Frequency [Hz]		60			60			
Rated voltage [V]		200			200			
Rated current [A]		138			49.2			
L. R. Amperes [A]		1210			217			
LRC [A]		8.8x(Code K)			4.4x(Code G)			
No load current [A]		70.6			37.5			
Rated speed [RPN	Л]	1780			885			
Slip [%]	-	1.11			1.67			
Rated torque [ft.lb	]	146			73.2			
Locked rotor torqu		310			190			
Breakdown torque [%]		350			229			
Service factor		1.25			1.25			
Temperature rise		80 K			80 K			
Locked rotor time		14s (cold) 8s (hot)			82s (cold) 46s (hot)			
Noise level <sup>2</sup>		70.0 dB(A)			60.0 dB(A)			
	25%	88.1			82.8			
Efficiency (%)	50%	89.5			82.8			
	50% 75%	91.0						
	100%				87.5			
		92.4			<u>88.5</u> 0.21			
Power Factor	25%	0.39						
	50%	0.67			0.40			
	75%	0.78			0.52			
	100%	0.84	1		0.61			
Bearing type		Drive end Non drive end	Founda	tion loads				
		6314 6314 Max. traction		iction	: 575 lb			
		2RS C3 2RS C3						
Sealing		: WSeal WSeal	Max. co	mpression	: 577 lb			
Lubrication interval		:						
Lubricant amour	it	:						
Lubricant type		: POLYREA ESTER						
		OIL (WT/ ENS)						
Notes								
This revision real	aces and car	ncel the previous one, which	These a	are average values	hased on tests wit	th sinusoidal		
must be eliminate								
(1) Looking the m		shaft end	MG-1.	ver supply, subject to the tolerances stipulated in NEMA				
		olerance of +3dB(A).						
		t to changes after						
manufacturing pro								
(4) At 100% of ful								
Rev.		Changes Summary		Performed	Checked	Date		
		Changes Summary			Checked	Date		
				<u> </u>				
Performed by								
-					Pane	Revision		
Checked by Date	18/01/201				Page 1 / 2	Revision		

 
 Date
 18/01/2018
 1 / 2

 This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
 1 / 2
Subject to change without notice

Three Phase Induction Motor - Squirrel Cage

Customer

:

## Space heater information

Voltage: 110-127/200-240 V

Rev.		Changes Summary	Performed	Checked	Date		
Performed by							
Checked by				Page	Revision		
Date	18/01/2018			2/2			
This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.							

Subject to change without notice

